

WRECKER

30CS

Built for demanding recoveries, the 30CS will quickly become a very handy unit in your fleet. It can tow pickup trucks to loaded tractor-trailers, and then some. Add a Tag Axle, and turn your 30CS into an unbeatable towing machine.

Slide the mast, extend the boom and perform recoveries you thought impossible, with an ease you have never experienced.

What more could you ask for? Reach, of course! Compare our 30CS to the same category competing model and be wowed by the lightweight, easy-to-use 2-stage boom.



WRECKER SPECIFICATIONS

- 30-Ton Rated lifting capacity
- Dual 30,000 lbs planetary winches
- Working hydraulic pressure 3000 PSI
- Composite body 101.5" wide (including fenders)

BOOM SPECIFICATIONS

- 2-stage 78" Sliding V-shaped recovery boom
- Boom structural rating fully retracted: 60,000 lbs
- Boom structural rating fully extended: 25,000 lbs
- Reach past tailgate: 169"
- Maximum Boom working height: 300"
- Range of elevation: 0° - 63°
- 360° sheave head

MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 14,600 lbs capacity
- Rear Axle: Minimum 40,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum CLA 146"
(from cab to center of rearmost axle)



30 TONS



30,000 LBS



169"



NETRUCKCENTER.COM

Sales: (603) 658-7171

Service: (603) 778-8158