

## WRECKER

# 40CS

The adventurous 40CS is the perfect everyday partner that will deliver results, mile per mile, pound per pound.

Featuring the Slider System, the relentlessly strong and perfectly balanced 40CS will allow you to focus on the job itself, not on the equipment. Its optional 3-stage boom can be adapted, transformed, and slid out to provide more reach, and possibilities.



### WRECKER SPECIFICATIONS

- 40-Ton Rated lifting capacity
- Working hydraulic pressure 3000 PSI
- Dual 40,000 lbs 2-speed planetary winches
- Composite body 101.5" wide (including fenders)

### BOOM SPECIFICATIONS

- Standard 2-stage 97" V-shaped recovery boom
- Optional 3-stage V-shaped recovery boom
- Boom structural rating fully retracted: 80,000 lbs
- Boom structural rating fully extended (2-stage): 30,000 lbs
- Boom structural rating fully extended (3-stage): 15,000 lbs
- Reach past tailgate (3-stage): 281"
- Maximum Boom working height (3-stage): 404"
- Range of elevation: 0° - 60°
- 360° sheave head

### MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 16,000 lbs capacity
- Rear Axle: Minimum 40,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum CLA 183" for tandem axle body (from cab to center of rearmost axle)
- Minimum CLA 200" for tri-axle body (from cab to center of rearmost axle)



40 TONS

CAPACITY



STANDARD  
WINCHES

40,000 LBS



BOOM REACH

281"

NETRUCKCENTER.COM

Sales: (603) 658-7171

Service: (603) 778-8158