

WRECKER

50CS

Perfect for the toughest jobs, the 50CS has a longer and stronger boom to give you more lifting power and increased reach. Take advantage of the Slider System to get the job done without compromising on towing capacity.

Reliable and resistant, this reckless titan will propel your business. And when we say 50-tons at NRC, we really mean 50-tons! The 50CS tackles everything. Go in strong with the 50CS ; once you've taken control, you won't be able to stop.



WRECKER SPECIFICATIONS

- 50-Ton Rated lifting capacity
- Dual 50,000 lbs 2-speed planetary winches
- Working hydraulic pressure 3000 PSI
- Composite body 101.5" wide (including fenders)

BOOM SPECIFICATIONS

- Standard 97" 2-stage V-shaped recovery boom
- Optional 3-stage V-shaped recovery boom
- Boom structural rating fully retracted: 100,000 lbs
- Boom structural rating fully extended (2-stage): 40,000 lbs
- Boom structural rating fully extended (3-stage): 20,000 lbs
- Reach past tailgate (3-stage): 281"
- Maximum Boom working height (3-stage): 411"
- Range of elevation: 0° - 60°

MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 18,000 lbs capacity
- Rear Axle: Minimum 46,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum CLA 183" for tandem axle body (from cab to center of rearmost axle)
- Minimum CLA 200" for tri-axle body (from cab to center of rearmost axle)



50 TONS



STANDARD
WINCHES

50,000 LBS



BOOM REACH

281"

