

156 Epping Road Exeter, NH 03833 800-261-7219

Stock Number: #2024 Western Star 47X 2024 White Western Star 47X

Details:

- 2023 NRC 30TB 28'
- Fully Galvanized Deck and Subframe
- Lodar Remote
- ≥ 20k Winch
- Detroit DD13
- > 505HP
- Allison 4500 RDS
- Full Chassis / Body spec attached

Price: 253,572



Exeter, NH 03833 Phone: 603-778-8158

SPECIFICATION PROPOSAL

Data	a Code	Description	Weight Front	Weight Rear	
Price Level					
PRL	-26X	WST 47X/49X PRL-26X (EFF:07/26/21)			
Data Versio	n				
DRL	-022	SPECPRO21 DATA RELEASE VER 022			
Vehicle Con	figuratio	n			
001-	470	WESTERN STAR 47X	9,050	6,525	
004-	223	2023 MODEL YEAR SPECIFIED			
002-	004	SET BACK AXLE - TRUCK			
019-	006	TRAILER TOWING PROVISION AT END OF FRAME WITH SAE J560	10	10	
003-	001	LH PRIMARY STEERING LOCATION			
General Ser	vice				
AA1	-003	TRUCK/TRAILER CONFIGURATION			
AA6	-001	DOMICILED, USA 50 STATES (INCLUDING CALIFORNIA AND CARB OPT-IN STATES)			
A85-	-002	PICKUP AND DELIVERY/SHORT HAUL SERVICE			
A84-	-1VT	VEHICLE TRANSPORTER BUSINESS SEGMENT			
AA4	-003	DRY BULK COMMODITY			
AA5	-002	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS			
AB1	-008	MAXIMUM 8% EXPECTED GRADE			
AB5	-001	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE			
995-	1A5	WESTERN STAR VOCATIONAL WARRANTY			
A66-	-99D	EXPECTED FRONT AXLE(S) LOAD: 14780.0 lbs			
A68-	-99D	EXPECTED REAR DRIVE AXLE(S) LOAD: 40000.0 lbs			
A63-	-99D	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 54780.0 lbs			

Prepared for:

Mike Lampert NEW ENGLAND TRUCK CENTER 156 Epping

	Data Code	Description	Weight Front	Weight Rear
,	A70-99D	EXPECTED GROSS COMBINATION WEIGHT: 80000.0 lbs		
Truck Se	ervice			
	AA3-005	FLATBED/PLATFORM/STAKE BODY		
	AF4-99D	EXPECTED EMPTY BODY WEIGHT: 0.0 lbs		
	A88-99D	EXPECTED TRUCK BODY LENGTH: 26.0 ft		
	AF3-151	NEW ENGLAND TRUCK EQUIPMENT		
Tractor \$	Service			
	AA2-001	VAN TRAILER		
į.	AH6-001	SINGLE (1) TRAILER		
Engine				
	101-3C1	DETROIT DD13 GEN 5 12.8L 505 HP @ 1625 RPM, 1900 GOV RPM, 1850 LB/FT @ 975 RPM		
Electron	ic Parameter	s		
	79A-075	75 MPH ROAD SPEED LIMIT		
	79B-001	CRUISE CONTROL SPEED LIMIT 1 MPH HIGHER THAN ROAD SPEED LIMIT		
	79F-013	FLEET MANAGEMENT - DAILY ENGINE USAGE ENABLED		
	79K-007	PTO MODE ENGINE RPM LIMIT - 1100 RPM		
	79P-032	PTO RPM CONTROL WITH STEERING WHEEL SWITCHES		
	79T-002	PTO MODE RPM INCREMENT - 50 RPM		
	79U-007	PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND		
	79W-012	ONE CLUSTER SELECTABLE PTO GOVERNOR ENGINE SPEED PARAMETER		
•	79X-001	PTO SPEED 1 SETTING - 700 RPM		
;	80C-012	ENGINE BRAKE WITH GLOBAL CRUISE CONTROL ENABLED		
	80D-001	SOFT CRUISE CONTROL ENABLED		
	80G-001	PTO MINIMUM RPM - 600		
;	80L-003	ENABLE DPF REGEN ZONE 1 WITH AUTO ENGINE RPM ELEVATE FOR EXTENDED IDLE		
*	80S-004	PTO 1, DASH SWITCH, ENGAGE WHILE DRIVING		
Engine E	Equipment			
	99C-021	2010 EPA/CARB/GHG21 CONFIGURATION		

Data Code	Description	Weight Front	Weight Rear	
 99D-011	2008 CARB EMISSION CERTIFICATION - CLEAN IDLE (INCLUDES 6X4 INCH LABEL ON LOWER FORWARD CORNER OF DRIVER DOOR)			
13E-001	STANDARD OIL PAN			
105-001	ENGINE MOUNTED OIL CHECK AND FILL			
014-116	SIDE OF HOOD AIR INTAKE WITH ENGINE MOUNTED AIR CLEANER			
124-105	LN 12V 170 AMP AVI 160 PAD MOUNT ALTERNATOR			
292-236	(3) DTNA GENUINE, FLOODED STARTING, MIN 3000CCA, 555RC, THREADED STUD BATTERIES	-10		
290-1CD	BATTERY BOX WITH ALUMINUM COVER MOUNTED SHORT SIDE TO RAIL	-50	10	
282-004	SINGLE BATTERY BOX FRAME MOUNTED RH SIDE BACK OF CAB			
291-017	WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN			
289-022	POLISHED ALUMINUM DIAMOND PLATE WST BATTERY BOX COVER			
107-046	BW MODEL FE-921 19.0 CFM SINGLE CYLINDER AIR COMPRESSOR WITH SAFETY VALVE			
152-041	ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM			
128-002	JACOBS COMPRESSION BRAKE			
016-1C3	RH OUTBOARD UNDER STEP MOUNTED HORIZONTAL AFTERTREATMENT SYSTEM ASSEMBLY WITH RH HORIZONTAL TAILPIPE	-30	-20	
28F-015	ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD ACTIVE REGENERATION AND VIRTUAL REGENERATION REQUEST SWITCH IN CLUSTER AND DASH MOUNTED INHIBIT SWITCH			
239-001	STANDARD EXHAUST SYSTEM LENGTH			
237-052	RH STANDARD HORIZONTAL TAILPIPE			
23U-002	13 GALLON DIESEL EXHAUST FLUID TANK	9	3	
23Z-007	POLISHED ALUMINUM DIAMOND PLATE WST DIESEL EXHAUST FLUID TANK COVER			
43X-001	LH HEAVY DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION			
43Y-001	STANDARD DIESEL EXHAUST FLUID TANK CAP			
273-059	ELECTRONICALLY CONTROLLED VARIABLE SPEED VISCOUS FAN DRIVE			



Data Code	Description	Weight Front	Weight Rear	
276-002	AUTOMATIC FAN CONTROL WITH DASH SWITCH AND INDICATOR LIGHT, NON ENGINE MOUNTED			
122-1H2	DETROIT FUEL/WATER SEPARATOR WITH BYPASS AND 12 VOLT PREHEATER	10		
110-068	DDC SUPPLIED ENGINE MOUNTED FUEL FILTER/FUEL WATER SEPARATOR WITH WATER-IN-FUEL INDICATOR			
118-001	FULL FLOW OIL FILTER			
266-107	1400 SQUARE INCH VOCATIONAL RADIATOR			
103-039	ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT			
171-007	GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT			
270-023	HDEP FIXED RATIO COOLANT PUMP AND RADIATOR DRAIN VALVE			
168-002	LOWER RADIATOR GUARD			
138-005	PHILLIPS-TEMRO 1500 WATT/115 VOLT BLOCK HEATER	4		
166-005	PHILLIPS-TEMRO 300 WATT/115 VOLT OIL PREHEATER	4		
140-022	CHROME ENGINE HEATER RECEPTACLE MOUNTED UNDER LH DOOR			
155-076	DELCO 12V MOD 3.175-39MT+ STARTER WITH ENGINE ECU SOFTWARE PROTECTION AND INTEGRATED MAGNETIC SWITCH	-45		
Transmission				
342-1M3	ALLISON 4500 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION			
Transmission Equ	ipment			
343-339	ALLISON VOCATIONAL PACKAGE 223 - AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV			
84B-012	ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES			
84C-023	PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84D-023	SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			

Rd Exeter, NH 03833 Phone: 603-778-8158

Data Code	Description	Weight Front	Weight Rear	
84E-013	S1 PERFORMANCE PRIMARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84F-012	S1 PERFORMANCE SECONDARY SHIFT SCHEDULE, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY			
84G-009	1800 RPM PRIMARY MODE SHIFT SPEED			
84H-009	1800 RPM SECONDARY MODE SHIFT SPEED			
85G-001	MAXIMUM OUTPUT SPEED FOR PTO ENGAGEMENT 50 RPM			
353-073	QUICKFIT BODY LIGHTING CONNECTOR UNDER CAB, WITH CAP			
34C-011	ELECTRONIC TRANSMISSION WIRING TO CUSTOMER INTERFACE CONNECTOR			
362-823	CUSTOMER INSTALLED CHELSEA 280 SERIES PTO			
363-001	PTO MOUNTING, LH SIDE OF MAIN TRANSMISSION ALLISON			
341-018	MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN			
345-003	PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED			
370-006	WATER TO OIL TRANSMISSION COOLER			
346-003	TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK			
35T-001	SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)			
Front Axle and Equ	uipment			
400-1AA	MFS-16-143A 16,000# FL1 71.5 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE	130		
418-060	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS	20		
402-030	MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES	10		
403-002	NON-ASBESTOS FRONT BRAKE LINING			
419-023	CONMET CAST IRON FRONT BRAKE DRUMS			
427-001	FRONT BRAKE DUST SHIELDS	5		
409-006	FRONT OIL SEALS			
408-016	STEMCO SERIES 340/343/346 TRADITIONAL ALUMINUM FRONT HUB CAPS WITH WINDOW AND RED VENT PLUGS - OIL			

Application Version 11.7.705 Data Version PRL-26X.022 NV 47x tandem ramp August 2022



Exeter, NH 03833 Phone: 603-778-8158

Data Code	Description	Weight Front	Weight Rear	
405-002	MERITOR AUTOMATIC FRONT SLACK ADJUSTERS			
536-103	SINGLE HIGH CAPACITY POWER STEERING GEAR, BENDIX, 14.6-18K	-18		
534-015	2 QUART SEE THROUGH POWER STEERING RESERVOIR			
40T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE			
Front Suspension				
620-026	16,000# TAPERLEAF FRONT SUSPENSION	135		
619-002	THREADED SPRING PINS AND BUSHINGS - FRONT SUSPENSION			
410-001	FRONT SHOCK ABSORBERS			
Rear Axle and Equip	ment			
420-1K4	MT-40-14XP 40,000# R-SERIES TANDEM REAR AXLE		20	
450-060	CONMET PRESET PLUS PREMIUM IRON REAR HUBS		60	
421-390	3.90 REAR AXLE RATIO			
424-003	IRON REAR AXLE CARRIER WITH OPTIONAL HEAVY DUTY AXLE HOUSING		40	
386-075	MXL 18T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES	40	40	
388-073	MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES			
452-006	DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES		30	
878-022	(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD- REAR AXLE VALVE AND (1) REAR-REAR AXLE VALVE			
87A-005	INDICATOR LIGHT FOR EACH INTERAXLE LOCKOUT SWITCH			
87B-009	INDICATOR LIGHT AND BUZZER FOR EACH DIFFERENTIAL LOCKOUT SWITCH			
423-020	MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES			
433-002	NON-ASBESTOS REAR BRAKE LINING			
434-005	BRAKE CAMS AND CHAMBERS ON FORWARD SIDE OF DRIVE AXLE(S) WITH AUXILIARY SUPPORT BRACKETS			
451-023	CONMET CAST IRON REAR BRAKE DRUMS			

Application Version 11.7.705 Data Version PRL-26X.022 NV 47x tandem ramp August 2022



Data Code	Description	Weight Front	Weight Rear	
425-002	REAR BRAKE DUST SHIELDS		10	
440-006	REAR OIL SEALS			
426-101	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS			
428-002	MERITOR AUTOMATIC REAR SLACK ADJUSTERS			
41T-002	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE			
42T-001	STANDARD REAR AXLE BREATHER(S)			
Rear Suspension				
622-005	AIRLINER 40,000# REAR SUSPENSION			
621-118	7.9 INCH NOMINAL RIDE HEIGHT (415MM GLOBAL REFERENCE HEIGHT)			
431-001	STANDARD AXLE SEATS IN AXLE CLAMP GROUP			
624-016	51 INCH AXLE SPACING			
888-078	IGNITION CONTROLLED ELECTRIC DUMP SWITCH FOR AIR SUSPENSION WITH STATE RETENTION AND GAUGE			
87D-011	REAR AIR SUSPENSION DUMP VALVE AUTOFILL >5 MPH WITH BUZZER AND INDICATOR LIGHT			
910-001	SINGLE AIR REAR SUSPENSION LEVELING VALVE			
623-002	TRANSVERSE CONTROL RODS			
439-005	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)			
Brake System				
490-1AU	WABCO 4S/4M ABS WITH TRACTION CONTROL WITH ATC SHUT OFF SWITCH			
871-001	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES			
432-003	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE			
480-040	WABCO SYSTEM SAVER 1200 HEATED AIR DRYER WITH PRESSURE CONTROL VALVE			
483-004	WABCO OIL COALESCING FILTER FOR AIR DRYER			
479-012	AIR DRYER MOUNTED UNDER HOOD			
460-001	STEEL AIR BRAKE RESERVOIRS			
477-019	BW DV-2 AUTO DRAIN VALVE WITH HEATER TO WET TANK; DRAIN VALVE CABLES ON ALL OTHER TANKS			

Prepared for:

Mike Lampert NEW ENGLAND TRUCK CENTER 156 Epping

Exeter, NH 03833 Phone: 603-778-8158

	Data Code	Description	Weight Front	Weight Rear	
Trailer	Connections				
	914-001	AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND NO DUST COVERS	5	5	
	296-010	PRIMARY CONNECTOR/RECEPTACLE WIRED FOR SEPARATE STOP/TURN, ABS CENTER PIN POWERED THROUGH IGNITION			
	303-025	SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME			
Wheel	base & Frame				
	545-727	7275MM (287 INCH) WHEELBASE			
	546-1C3	11.0MM X 85.0MM X 287.0MM STEEL FRAME (0.43X3.35X11.30 INCH) 120 KSI	600	220	
	552-029	1575MM (62 INCH) REAR FRAME OVERHANG			
	55W-006	FRAME OVERHANG RANGE: 61 INCH TO 70 INCH	-30	80	
	AC8-99D	CALC'D BACK OF CAB TO REAR SUSP C/L (CA): 221.26 in			
	AE4-99D	CALC'D FRAME LENGTH - OVERALL: 393.57 in			
	ZF1-99D	FRAME HEIGHT TOP FRONT UNLADEN: 40.04 in			
	ZF2-99D	FRAME HEIGHT TOP FRONT LADEN: 37.65 in			
	ZF3-99D	FRAME HEIGHT TOP REAR UNLADEN: 37.67 in			
	ZF4-99D	FRAME HEIGHT TOP REAR LADEN: 35.7 in			
	553-001	SQUARE END OF FRAME			
	559-001	STANDARD WEIGHT ENGINE CROSSMEMBER			
*	561-007	HEAVY DUTY BACK OF TRANSMISSION CROSSMEMBER	10		
N	562-028	HEAVY DUTY MIDSHIP #1 CROSSMEMBER	10	10	
N	572-036	HEAVY DUTY REAR CROSSMEMBER		70	
N	565-001	STANDARD SUSPENSION CROSSMEMBER		20	
*	568-011	INVERTED MOUNTED REAR SUSPENSION CROSSMEMBER AFT 46 INCHES FROM REAR SUSPENSION CENTERLINE			
Chass	is Equipment				
	025-003	POLISHED ALUMINUM DIAMOND PLATE WST EQUIPMENT COVERS			
	5CF-001	CLEAR FRAME SPACE REQUESTED			
*	6CF-001	1 MID CHASSIS COMPONENT LOCATION REQUEST			

Application Version 11.7.705 Data Version PRL-26X.022 NV 47x tandem ramp August 2022



MOUNT AIR TANKS 50" FORWARD OF THE STAND ARD LOCATION PLEASE

Phone: 603-778-8158



Weight Weight **Data Code** Description Front Rear 556-127 BRIGHT STEEL 1/8 INCH VOCATIONAL BUMPER REMOVABLE FRONT TOW/RECOVERY 558-070 DEVICE, STORED ON CHASSIS FRAME BUMPER MOUNTING FOR SINGLE LICENSE 574-001 **PLATE** Ν 551-032 CLASS 10.9 THREADED METRIC FASTENERS; REAR SUSPENSION HANGER TO BE HUCK-SPIN 44Z-002 EXTERIOR HARNESSES WRAPPED IN **ABRASION TAPE Fuel Tanks** 204-154 80 GALLON/302 LITER ALUMINUM FUEL TANK -10 LH 218-006 25 INCH DIAMETER FUEL TANK(S) 215-006 POLISHING OF FUEL/HYDRAULIC TANK(S) WITH POLISHED STAINLESS STEEL BANDS 212-007 FUEL TANK(S) FORWARD 664-002 POLISHED STEP FINISH CHROME FUEL TANK CAP(S) 205-002 216-020 **EQUIFLO INBOARD FUEL SYSTEM** 202-016 HIGH TEMPERATURE REINFORCED NYLON **FUEL LINE Tires** MICHELIN X LINE ENERGY Z 295/60R22.5 18 PLY -12 093-1VT RADIAL FRONT TIRES CONTINENTAL HDL2+ ECO PLUS 295/60R22.5 18 094-10T -48 PLY RADIAL REAR TIRES Wheels 502-664 ALCOA ULTRA ONE 89U63X 22.5X9.00 10-HUB -44 PILOT 3.12 INSET 10-HD ALUMINUM FRONT WHEELS ALCOA ULTRA ONE 89U64X 22.5X9.00 10-HUB 505-356 PILOT 5.99 INSET ALUMINUM REAR WHEELS POLISHED DISC SIDE FRONT WHEELS WITH 524-022 **DURA-BRIGHT FINISH** 525-023 POLISHED OUTER (DISHED SIDE) REAR WHEELS WITH OUTER ONLY DURA-BRIGHT **FINISH** 496-011 FRONT WHEEL MOUNTING NUTS 497-011 REAR WHEEL MOUNTING NUTS

Cab Exterior

Data Code	Description	Weight Front	Weight Rear	
829-053	111.6 INCH BBC CONVENTIONAL ALUMINUM CAB			
82A-028	STAINLESS STEEL CAB ACCENT MOLDING			
667-001	FRONT FENDERS			
754-017	BOLT-ON MOLDED FLEXIBLE FENDER EXTENSIONS	10		
678-066	INTERIOR GRAB HANDLES WITH ADDED LOWER LH AND RH A PILLAR GRAB HANDLES AND LH AND RH EXTERIOR NON-SLIP GRAB HANDLES			
65X-010	BRIGHT HOOD MOUNTED AIR INTAKE GRILLE, BLACK SCREEN, WITH LED ACCENT LIGHTS			
640-016	X-SERIES STEEL REINFORCED ALUMINUM CAB			
644-048	X-SERIES VOCATIONAL HOOD			
67U-001	HOOD OPENING ASSIST WITH LOCKING STRUT			
652-016	WESTERN STAR NAMEPLATES			
727-039	FOUR HADLEY SD-978 26 INCH RECTANGULAR AIR HORNS	8		
726-001	SINGLE ELECTRIC HORN			
575-001	REAR LICENSE PLATE MOUNT END OF FRAME			
327-012	SWITCH, INDICATOR LIGHT AND WIRING FOR (2) CUSTOMER FURNISHED BEACONS	2		
312-095	DUAL STAGE INTELLIGENT LED HEADLIGHTS WITH HEATED LENS SYSTEM			
302-073	VISOR MOUNTED LED MARKER LIGHTS			
311-001	DAYTIME RUNNING LIGHTS			
294-1AY	INTEGRAL LED STOP/TAIL/BACKUP LIGHTS			
300-043	LED SIDE TURN SIGNAL			
744-106	C-BAR MIRROR SYSTEM WITH DUAL HEATED MIRRORS WITH INTEGRAL HEATED CONVEX, DUAL REMOTE, STAINLESS STEEL BACK COVER, AND BLACK C-BAR			
796-001	102 INCH EQUIPMENT WIDTH			
743-209	LH AND RH CONVEX MIRRORS INTEGRAL WITH PRIMARY MIRRORS			
74A-001	RH DOWN VIEW MIRROR			
729-001	STANDARD SIDE/REAR REFLECTORS			
677-100	POLISHED ALUMINUM DIAMOND PLATE WST AFTERTREATMENT SYSTEM COVER			
764-020	STAINLESS STEEL EXTERIOR SUN VISOR WITH INTEGRAL MARKER LIGHTS	16		

Data Code	Description	Weight Front	Weight Rear	
768-064	SINGLE SOLAR TINTED REAR WINDOW, (1) 31 INCH X 20 INCH			
663-019	1-PIECE ROPED-IN SOLAR GREEN GLASS WINDSHIELD			
659-006	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR			
Cab Interior				
055-016	X-SERIES PREMIUM INTERIOR TRIM LEVEL PACKAGE			
707-1C4	CHARCOAL BLACK VINYL UP LEVEL INTERIOR			
70K-017	CARBON WITH PREMIUM TEAK ACCENT			
772-035	BLACK MATS WITH ADDED FLOOR HEAT AND NOISE INSULATION			
785-014	(2) DASH MOUNTED POWER OUTLETS AND COIN TRAY			
691-001	FORWARD ROOF MOUNTED CONSOLE			
693-019	LH AND RH DOOR STORAGE POCKETS INTEGRATED INTO MOLDED DOOR PANELS			
741-015	(2) COAT HOOKS ON BACKWALL OF CAB			
738-021	DIGITAL ALARM CLOCK IN DRIVER DISPLAY			
720-035	2-1/2 LB. FIRE EXTINGUISHER MOUNTED INBOARD OF DRIVER SEAT	5		
170-045	STANDARD HEATER PLUMBING WITH BALL SHUTOFF VALVES AT SUPPLY LINES ONLY			
698-001	RADIATOR MOUNTED AIR CONDITIONER CONDENSER			
739-034	PREMIUM INSULATION			
324-1B2	PREMIUM LED CAB LIGHTING			
787-998	NO SECURITY DEVICE			
657-001	DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME			
78G-004	KEY QUANTITY OF 4			
655-028	LH AND RH ELECTRIC DOOR LOCKS WITH AUTO UNLOCK FEATURE WHEN DOOR IS SET FROM OPEN TO CLOSED POSITION			
64C-003	BLACK DOOR HANDLES			
722-028	TRIANGULAR REFLECTORS KIT WITHOUT FLARES SHIPPED LOOSE IN CAB	10		



Prepared for: Mike Lampert NEW ENGLAND TRUCK

CENTER 156 Epping Rd

Data Code	Description	Weight Front	Weight Rear	
756-1J6	PREMIUM 2.0 HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 2 AIR LUMBAR, INTEGRATED CUSHION EXTENSION, TILT AND ADJUSTABLE SHOCK	20		
760-1J6	PREMIUM 2.0 HIGH BACK AIR SUSPENSION PASSENGER SEAT WITH 2 AIR LUMBAR, INTEGRATED CUSHION EXTENSION, TILT AND ADJUSTABLE SHOCK	40	15	
757-002	BLACK SUSPENSION COVER FOR DRIVER AND PASSENGER SEATS	4		
759-007	DUAL DRIVER SEAT ARMRESTS, NO PASSENGER SEAT ARMRESTS			
758-131	BLACK LAREDO LEATHER DRIVER SEAT COVER WITH DIAMOND STITCHED CENTER PANELS AND EMBROIDERED LOGO			
761-131	BLACK LAREDO LEATHER PASSENGER SEAT COVER WITH DIAMOND STITCHED CENTER PANELS AND EMBROIDERED LOGO			
763-1AA	3 POINT ADJUSTABLE D-RING RETRACTOR DRIVER AND FIXED D-RING RETRACTOR PASSENGER SEAT BELTS			
532-002	ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN			
540-070	4-SPOKE 18 INCH (450MM) LEATHER WRAPPED STEERING WHEEL WITH CHROME SWITCH BEZELS			
765-021	DRIVER AND PASSENGER INTERIOR SUN VISORS WITH ILLUMINATED VANITY MIRRORS			
Instruments & Co	ntrols			
015-006	STOCK TRUCK/UPFIT PACKAGE LVL 1			
185-004	STANDARD FOOT PEDAL SYSTEM			
106-002	ELECTRONIC ACCELERATOR CONTROL			
870-002	BRIGHT ARGENT FINISH GAUGE BEZELS			
734-018	STANDARD CENTER INSTRUMENT PANEL			
838-001	(1) SINGLE BRAKE APPLICATION AIR GAUGE			
840-001	DUAL NEEDLE PRIMARY AND SECONDARY AIR PRESSURE GAUGE			
198-025	INTAKE MOUNTED AIR RESTRICTION INDICATOR WITHOUT GRADUATIONS			
721-001	97 DB BACKUP ALARM		3	
149-015	ELECTRONIC CRUISE CONTROL WITH CONTROLS ON STEERING WHEEL SPOKES			

Da	ata Code	Description	Weight Front	Weight Rear	
15	56-007	KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY			
33	39-007	AUXILIARY POWER DISTRIBUTION MODULE FOR TEM USE, AUXILIARY EVAULT MOUNTED, CIRCUIT BREAKER PROTECTED			
81	11-044	PREMIUM INSTRUMENT CLUSTER WITH 5.0 INCH TFT COLOR DISPLAY			
81	IB-003	DIGITAL PANEL LAMP DIMMER SWITCH IN DRIVER DISPLAY			
16	60-045	HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR WITH DUST CAP LOCATED BELOW LH DASH			
84	14-001	2 INCH ELECTRIC FUEL GAUGE			
84	15-011	FUEL FILTER RESTRICTION INDICATOR			
14	18-072	ENGINE REMOTE INTERFACE WITH MULTIPLE SET SPEEDS			
86	66-009	DUAL REAR AXLE TEMPERATURE GAUGES WITH SENSOR SHIELD			
85	56-001	ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE			
85	54-001	ENGINE OIL TEMPERATURE GAUGE			
85	52-002	ELECTRIC ENGINE OIL PRESSURE GAUGE			
86	64-001	2 INCH TRANSMISSION OIL TEMPERATURE GAUGE			
86	67-004	ELECTRONIC OUTSIDE TEMPERATURE SENSOR DISPLAY IN DRIVER MESSAGE CENTER			
83	30-031	ENGINE, TRIP AND PTO HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY			
37	72-123	PTO CONTROLS FOR ENHANCED VEHICLE ELECTRIC/ELECTRONIC ARCHITECTURE			
73	36-998	NO OBSTACLE DETECTION SYSTEM			
49	9B-998	NO VEHICLE STABILITY ADVISOR OR CONTROL			
73	3B-998	NO LANE DEPARTURE WARNING SYSTEM			
35	5M-010	QUICKFIT PROGRAMMABLE INTERFACE MODULE	10		
67	ΓS-005	TMC RP1226 ACCESSORY CONNECTOR LOCATED BEHIND PASSENGER SIDE REMOVEABLE DASH PANEL			
74	16-135	AM/FM/WB WORLD TUNER RADIO WITH SIRIUSXM, BLUETOOTH, IPOD INTERFACE, USB AND AUXILIARY INPUTS, J1939			
74	17-001	DASH MOUNTED RADIO			

Data Code	Description	Weight Front	Weight Rear	
750-041	STANDARD SPEAKER SYSTEM			
753-998	NO AM/FM RADIO ANTENNA			
748-044	UNIDEN PC78LTX FACTORY INSTALLED CB RADIO WITH SWR METER	5		
749-001	ROOF/OVERHEAD CONSOLE CB RADIO PROVISION			
751-998	NO SPEAKER/LEAD FOR 2-WAY RADIO			
752-004	SINGLE FIBERGLASS LH MIRROR MOUNTED CB ANTENNA WITH BRACKET AND LEAD			
75W-001	HEADLINER MULTI-BAND ANTENNA: AM/FM/WEATHERBAND, WIFI/BLUETOOTH, GNSS/GPS			
78C-003	INTEROPERABLE SDAR ANTENNA			
810-027	ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER			
812-032	ELECTRONIC 2500 RPM TACHOMETER			
813-1C8	DETROIT CONNECT PLATFORM HARDWARE			
8D1-205	5 YEARS DETROIT CONNECT BASE PACKAGE (FEATURES VARY BY MODEL) DETROIT CONNECT PLATFORM			
162-002	IGNITION SWITCH CONTROLLED ENGINE STOP			
329-133	FOUR EXTRA HARDWIRED SWITCHES IN DASH, ROUTE TO BETWEEN SEATS, BLUNTCUT			
4C1-025	HARDWIRE SWITCH #1, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
4C2-025	HARDWIRE SWITCH #2, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
4C3-016	HARDWIRE SWITCH #3, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
4C4-016	HARDWIRE SWITCH #4, ON/OFF LATCHING, 20 AMPS IGNITION POWER			
81Y-005	PRE-TRIP INSPECTION FEATURE FOR EXTERIOR LAMPS ONLY			
482-001	BW TRACTOR PROTECTION VALVE			
883-028	TRAILER HAND CONTROL BRAKE VALVE AND WINCH BRAKE (APPLIES 45 PSI AIR TO STEER AXLE SERVICE BRAKES WHEN PARKED)			
842-001	2 INCH TURBO AIR PRESSURE GAUGE			
836-015	DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY			

Prepared for: Mike Lampert NEW ENGLAND TRUCK

CENTER 156 Epping

ROTARY HEADLAMP SWITCH, MARKER LIGHTS/HEADLGHTS SWITCH WITH PULL OUT FOR OPTIONAL FOG/ROAD LAMPS 882-004 TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR 299-020 SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP PLASH, WASHWIPE/INTERMITTENT 48H-004 QUICKFIT POWENTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS * 4CH-005 5 EXTRA PROGRAMMABLE SWITCHES/INDICATORS SA1A0000ZZ_A1B0000ZZ_A1C0000ZZ_A1E0000ZZ_A1E0000ZZ 48C-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 4CH-005 5 EXTRA PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 4CH-005 5 EXTRA PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 4CH-005 5 EXTRA PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 4BC-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 4BC-004 PAINT: * O65-000 PAINT: ONE SOLID COLOR **Color** 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT **Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS **SECONDARY FACTORY OPTIONS **SECONDARY FACTORY OPTIONS **SECONDARY FACTORY OPTIONS **SECONDARY FACTORY OPTIONS **O5-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QU		Data Code	Description	Weight Front	Weight Rear
WARNING INDICATOR 299-020 SELF CANCELING TURN SIGNAL SWITCH WITH DIMMER, HEADLAMP FLASH, WASHAWPE/INTERMITTENT 48H-004 QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS * 4CH-005 5 EXTRA PROGRAMMABLE SWITCHES/INDICATORS \$A1A00002Z_A1C00002Z_A1C0000ZZ_A1D0000ZZ_A1E0000ZZ 4BC-0004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 986-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS * 986-000 PAINT: ONE SOLID COLOR * Q80-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT * Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS * Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXILE IS RAISED * 516-154 295/60R22_5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY		304-030	LIGHTS/HEADLIGHTS SWITCH WITH PULL OUT		
DIMMER, HEADLAMP FLASH, WASHWIPPINTERMITTENT 48H-004 QUICKFIT POWERTRAIN INTERFACE CONNECTOR UNDER CAB WITH BLUNTCUTS • 4CH-005 \$ EXTRA PROGRAMMABLE SWITCHES/INDICATORS \$A1A0000ZZ, A1B0000ZZ, A1C0000ZZ, A1E0000ZZ 48C-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS Design 065-000 PAINT: ONE SOLID COLOR Color 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PILMS9S; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED • 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		882-004			
CONNECTOR UNDER CAB WITH BLUNTCUTS 4CH-005 5 EXTRA PROGRAMMABLE SWITCHES/INDICATORS \$A1A0000ZZ,A1B0000ZZ,A1C0000ZZ,A1E0000ZZ 48C-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS Design 065-000 PAINT: ONE SOLID COLOR Color 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		299-020	DIMMER, HEADLAMP FLASH,		
SWITCHES/INDICATORS \$A140000ZZ,A180000ZZ,A10000ZZ,A1D0000ZZ 48C-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS Design 065-000 PAINT: ONE SOLID COLOR Color 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#39S; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60722.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		48H-004			
### ABC-004 QUICKFIT PROGRAMMABLE INTERFACE CONNECTOR(S) UNDER CAB WITH BLUNTCUTS Design	*	4CH-005			
Design 065-000 PAINT: ONE SOLID COLOR Color 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		9	\$A1A0000ZZ,A1B0000ZZ,A1C0000ZZ,A1D0000ZZ ,A1E00	000ZZ	
065-000		48C-004			
Color 980-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE	Design				
986-5F6 CAB COLOR A: L0006EY WHITE ELITE EY 986-020 BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		065-000	PAINT: ONE SOLID COLOR		
BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE	Color				
PAINT Certification / Compliance 996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		980-5F6	CAB COLOR A: L0006EY WHITE ELITE EY		
996-001 U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		986-020			
Secondary Factory Options 999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE	Certific	ation / Com	pliance		
999-034 DEALER ADVISED AND ACCEPTS TERMS OF PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE APPLY		996-001			
PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE AXLE IS RAISED * 516-154 295/60R22.5 18 PLY RADIAL REAR TIRES RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE	Second	lary Factory	Options		
RPQ-002 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		999-034	PIL#395; SPEED OF LOADED VEHICLE MUST BE LIMITED TO 5 MPH MAXIMUM WHEN LIFTABLE		
APPLY RPQ-003 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE	*	516-154	295/60R22.5 18 PLY RADIAL REAR TIRES		
APPLY RPQ-004 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		RPQ-002			
APPLY RPQ-005 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		RPQ-003			
APPLY RPQ-006 RESERVED FOR SPECPRO PRICE QUOTE APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		RPQ-004	455174		
APPLY RPQ-007 RESERVED FOR SPECPRO PRICE QUOTE		RPQ-005			
		RPQ-006			
· · · - ·		RPQ-007	RESERVED FOR SPECPRO PRICE QUOTE APPLY		

Prepared for:

Mike Lampert NEW ENGLAND TRUCK CENTER 156 Epping

Rd

Exeter, NH 03833 Phone: 603-778-8158

Data Code	Description	Weight Front	Weight Rear	
Raw Performance	Data			
5LA-028	CFS,LH,OB,#1,START 28" BOC			
5LB-099	CFS,LH,OB,#1, 99" LONG			
5MA-011	CFS,RH,OB,#1,START 11" BOC			
5MB-099	CFS,RH,OB,#1, 99" LONG			
Sales Programs				
	NO SALES PROGRAMS HAVE BEEN SELECTED			

TOTAL VEHICLE SUMMARY

Weight Summary			
	Weight	Weight	Total
	Front	Rear	Weight
Factory Weight ⁺	9953 lbs	7103 lbs	17056 lbs
Total Weight ⁺	9953 lbs	7103 lbs	17056 lbs

If weight is critical, contact Customer Application Engineering.

⁽⁺⁾ Weights shown are estimates only.

^(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address	
New England Truck Center 156 Epping Road Exeter, NH 03833	

Date	Estimate #			
1/5/2023	457289			

PO#

OP#

		457289		STOCK
Item	Description	Qty		Total
Chassis	2024 RED WESTERN STAR 47X VIN# UM4206 FET INCLUDED		1	167,609.00
Bodies	2023 30TB-28' SERIAL# TBD		1	57,685.00
FET Payable	BODY FET		1	9,071.11
C-NC20	30 000 TB		1	0.00
C-3028	28'-30 000-TB		1	0.00
C-NC46	COMPLETE EQUIPMENT		1	0.00
C-D415	5 CHAIN SLOTS PER SIDE (18 TOTAL FOR 25', 26', 27', 28', 29', 30')		1	0.00
C-D44-4	SINGLE ROW OF (4) EXTRA CHAIN SLOTS IN THE CENTER OF DECK		1	0.00
C-D117-1	3/16" CHECKER PLATE DECK (STANDARD)		1	0.00
C-DISCLAIMER	CUSTOMER, FINAL PURCHASER OR END USER HAS BEEN INFORMED OF THE RISKS AND BENEFITS OF HOT DIP GALVANIZING (HDG) OF HIS NRC CAR CARRIER DECK		1	0.00
C-C3	FLAT TOP DECK WITH STAKE POCKET, WITHOUT REMOVABLE RAILS		1	0.00
C-B3S	3" HIGH X 9" SPACING (STANDARD FOR 30 000-TB AND 40 000-TB)		1	0.00
C-L16	5 MARKER LIGHTS PER SIDE		1	0.00
C-T04	DP 20,000 LBS WITH 5/8" X 75' WIRE ROPE (OPTION FOR 30 000-TB)		1	0.00
C-NC30	75' STEEL WIRE ROPE		1	0.00
C-CR01	SWIVEL HOOK		1	0.00
C-NC25	TANDEM AXLE		1	0.00
C-12V	12V WIRING		1	0.00
C-NC45	SUPER MEDIUM DUTY STINGER WITH 4X4 T-BAR (STANDARD FOR 30 000-TB)		1	0.00
C-G20	GALVANIZED SUB-FRAME AND BUMPER		1	0.00
C-NC17	CLEAR MARKER LIGHT		1	0.00
		Total		

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address
New England Truck Center 156 Epping Road Exeter, NH 03833

Date	Estimate #		
1/5/2023	457289		

PO#

OP#

		457289		STOCK
Item	Description	Qty		Total
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON BUMPER		1	0.00
C-NC11	LEVER CONTROL STANDARDS		1	0.00
C-S052	STAINLESS ON REAR BUMPER		1	0.00
C-G012	STABILIZER GRIP (30,000 & 40,000 LBS) (4X4)		1	0.00
C-L112-1	2 LED WORK LIGHTS ON TOP OF THE REAR BUMPER		1	0.00
C-A432	TRAILER HITCH & PINTLE HOOK ADAPTOR (4 HOLES) (T-BAR 4X4)		1	0.00
C-A1	STANDARD CHAIN RACK		1	0.00
C-A12	STD WINCH EMBEDDED IN CHAIN RACK		1	0.00
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON CHAIN RACK		1	0.00
C-NC40	CHAIN RACK NRC BLACK PAINT		1	0.00
C-S093	STAINLESS ON SIDES AND HEAD OF CHAIN RACK		1	0.00
C-L112-1	2 LED WORK LIGHTS ON TOP OF THE CHAIN RACK		1	0.00
C-LO6P	WIRELESS REMOTE CONTROL LODAR 6 BUTTONS		1	0.00
C-A421	RECOVERY ROLLER GUIDE (ROLLBACK)		1	0.00
C-S056	STAINLESS ON OIL TANK		1	0.00
C-NC110	WIRED TOWLIGHT ONLY		1	0.00
C-T6	TOUCHPAD WITH FUSELESS LIGHTING SYSTEM CONTROLLER		1	0.00
C-P-O	NO NEW CUSTOM REQUEST		1	0.00
C-NC26	"BLACK POLYMER CONTROL BOXES (STANDARD)		1	0.00
C-RACK6	74" (1880MM) - HEIGHT ABOVE FRAME RAILS (C#6)		1	0.00
C-PGAL-2	DECK GALVANIZED (OPTION FOR 24'-30' DECKS)		1	0.00
	UNCONFIGURABLE ITEMS			
DESTTRANSPORT	DESTINATION TRANSPORT CHARGE		1	1,300.00
DEALERINSTALL	DEALER INSTALL W/ PTO		1	9,750.00
72AMBJUSTLB-INST	72" AMBER JUSTICE LIGHT BAR INSTALLED		1	2,050.00
TU823503-INST	48" STAINLESS TOOLBOX INSTALLED		1	1,380.64
TU824003-INST	60" STAINLESS TOOLBOX INSTALLED		3	4,726.92
		Total		

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address	
New England Truck Center 156 Epping Road Exeter, NH 03833	

Date	Estimate #		
1/5/2023	457289		

OP#	PO #		
457289	STOCK		
Qty	Total		

ltem	Description	Qty	Total
	TOOLBOX LAYOUT MAY CHANGE ONCE CHASSIS ARRIVES AND FINAL MEASUREMENTS CAN BE TAKEN STANDARD STOCK PAINT/DETAIL 40TB INSTALL KIT	1	0.00
		Total	\$253,572.67

ONCE THE BUYER ACCEPTS THIS ORDER, THE BUYER'S DEPOSIT IS NOT REFUNDABLE UNLESS THE BUYER CANNOT TAKE DELIVERY OF SAID VEHICLE(S) FOR A REASON BEYOND THE BUYER'S CONROL. IN THAT EVENT, THE DEALER MAY, BUT WILL NOT BE REQUIRED TO, RETURN THE DEPOSIT TO THE BUYER, LESS ANY EXPENSES WHICH THE DEALER HAS INCURRED IN ACCEPTING AND PROCESSING THIS ORDER. THE BUYER'S FAILURE TO OBTAIN FINANCING BEFORE SCHEDULED DELIVERY IS NOT A REASON BEYOND THE BUYER'S CONTROL. THE BUYER WILL ALSO BE SUBJECT TO ANY PRICE INCREASES THAT ARE RECEIVED BY THE DEALER PERTAINING TO THE CHASSIS OR BODY. BY SIGNING THIS THE BUYER ACKNOWLEDGES HAVING READ AGREEING TO THESE TERMS AND CONDITIONS.



Terms & Conditions

- Once the buyer accepts this order, the buyer's deposit is not refundable unless the
 buyer cannot take delivery of the said vehicle(s) for a reason beyond the buyer's
 control. In that event, the dealer may, but will not be required to return the
 deposit to the buyer, less any expenses which the dealer has incurred in accepting
 and processing this order. The buyer's failure to obtain financing before scheduled
 delivery is not a reason beyond the buyer's control.
- The buyer will be subject to any price increase and or surcharge that are received by the dealer pertaining to the chassis or body.
- The buyer will be subject to any price increase on raw materials / parts that are incurred from the time of placing the order to the actual time of build and delivery of the unit(s).
- By signing this the buyer acknowledges having read and agreeing to these terms and conditions.

Date:			
Signature of Purchase	er:		
Opp#	Chassis:	 Body:	
NETC Representative:			

"Everything Truck"