

THE UTMOST OF
STRENGTH & CAPABILITIES



40TB



40,000 LBS



AVAILABLE
BED LENGTH

24' - 30'



STANDARD
WINCH

20,000 LBS

NRC 

NRC-INDUSTRIES.COM

CARRIER

40TB

Ever since the first NRC unit was conceived, we have built equipment that challenge what is possible. With their strong and sturdy construction, NRC Carriers make recoveries safer and easier. You focus on work. We'll focus on safety.

One call after the other, the 40TB can move mountains. Its reinforced deck beams, rigid cross-members and oversized subframe components push the limit of what a carrier can haul in a day, every single day.



CARRIER SPECIFICATIONS

- Tow bar lift rating: 20,000 lbs@0" / 10,000 lbs@58"
- Tow rating: 50,000 lbs | Deck rating: 40,000 lbs
- Operating pressure: 2,600 psi
- Deck width: 102"

STANDARD EQUIPMENT

- Standard winch: 20,000 lbs planetary
- Dual controls - lever type
- Pressure gauge
- Independant hydraulic tow bar
- Fixed headboard with chain rack (winch embedded in chain rack)
- 3 marker lights & 5 chain slots per side
- Hydraulic oil tank with filter - 12 GAL
- Hydraulic gear pump, direct mount - 17 GPM

MINIMUM FRAME REQUIREMENTS

- Cab to last axle : 196" - 274"
- Minimum RBM for tandem: 2,500,000 lbs-in / rail

DEALER:

NRC 

NRC-INDUSTRIES.COM

Tel: 450 379-5796 | Fax: 450 379-5995