

# QUICKSWAP & TAG









8,000 LBS



### **DETCHABLE UNIT**

## QUICKSWAP & TAG AXLE

The Quickswap & Tag Axle isn't just in a class of its own. It's started its own class. A sturdy and simple detachable design that turns into an innovative solution to propel your business.

Combined to a Tag Axle, your Quickwap will tow the world and stop on a dime. The additional set of brakes makes you stay in control, while the adjustable air ride suspension gives you outstanding driveability. 3 words: versatile, powerful, and profitable.





#### **QUICKSWAP & TAG SPECIFICATIONS**

- Towing capacity: 80,000 lbs
- Underlift lifting capacity: 35,000 lbs

- Tag Axle capacity: 17,000 lbs
- Additional set of brakes

#### STANDARD EQUIPMENT

- 3-stage HD Underlift
- Hydraulic underlift extension
- Hydraulic tilt boom
- Hydraulic fold
- Single oversized cylinder for underlift elevation
- Liftable air ride suspension
- Front and rear receivers (permanently mounted)
- 215/70R17.5 radial tires w/ dual steel wheels
- Aluminum fenders
- Safety chain pockets

#### MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 12,000 lbs capacity
- Rear Axle: Minimum 40,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum wheelbase: 250" HD Underlift
- Minimum wheelbase: 275" SHD Underlift

**DEALER:** 



**NRC-INDUSTRIES.COM** 

Tel: 450 379-5796 | Fax: 450 379-5995