

THE TOUGHEST
DETACHABLE UNIT
IN THE INDUSTRY



QUICKSWAP


UNDERLIFT
RATING

35,000 LBS+


TOW
RATING

80,000 LBS


BASIC
WEIGHT

6,000 LBS

NRC 
NRC-INDUSTRIES.COM

DETACHABLE UNIT

QUICKSWAP

Efficient in every sense of the word, the Quickswap saves big on fuel and maintenance costs while maximizing the possibilities... and your profits.

Quickswap's tough components and lightweight design make it a true workhorse. Add a winch to your Quickswap and use it as a supporting recovery unit.

Take advantage of the detachable design to push your limits during high seasons, and adapt during slower periods.



QUICKSWAP SPECIFICATIONS

- Towing capacity: 80,000 lbs
- Underlift lifting capacity: 35,000 lbs
- Basic weight: 6000 lbs
- Dual cylinders for underlift elevation

STANDARD EQUIPMENT

- 3-stage HD Underlift
- Hydraulic underlift extension
- Hydraulic tilt boom
- Hydraulic fold
- Removable front stands
- Manual controls
- Safety chain pockets
- Aluminum fenders
- Fork storage and holders
- Tie-down chains

MINIMUM FRAME REQUIREMENTS

- Front Axle: Minimum 12,000 lbs capacity
- Rear Axle: Minimum 40,000 lbs capacity
- Minimum frame RBM: 3,250,000 in.lbs per rail
- Minimum wheelbase: 250" HD Underlift
- Minimum wheelbase: 275" SHD Underlift

DEALER:



NRC-INDUSTRIES.COM

Tel: 450 379-5796 | Fax: 450 379-5995