

156 Epping Road Exeter, NH 03833 800-261-7219

Stock Number: STOCK PB 567 LJ

2025 Peterbilt 567 LJ

Details:

- 2024 NRC 40TB 28'
- Wooden Deck and Galvanized Subframe
- Lodar Remote
- > 20k Winch
- Cummins X15
- > 525HP
- ➤ Allison 4500 RDS-P Gen-6
- Full Chassis / Body spec attached

Price: \$333,000



Vehicle Summary

	Unit		Chassis	
Model:		Model 567	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs):	40000
Description 1:		CAR specs	G.C.W. (lbs):	80000
Description 2:		Copy of 567 lj		
	Application		Road Conditions:	
Intended Serv.:		Wrecker	Class A (Highway)	100
Commodity:	Transpo	rtation Equipment	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Type:	F	Platform w/Devices	Maximum Grade:	6
Length (fl):		24	Wheelbase (in):	309
Height (ft):		12	Overhang (in):	60
Max Laden Weight (lbs):		5000	Fr Axle to BOC (in):	90.1
			Cab to Axle (in):	218.9
	Trailer		Cab to EOF (in):	278.9
No. of Trailer Axles:		0	Overall Comb. Length (in):	400
Type:			. ,	
Length (ft):		0	Special Req.	
Height (ft):		0	•	
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		
Approved by:			Date:	

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2024

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

ales ode	Std/ Opt	Description	\$ List	Weigh
Base Mo	del			
0005671	S	Model 567 The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	207,933	14,80
0091170	0	Transportation Equipment	0	
0093110	0	Wrecker Truck with recovery body used for recovering and towing stranded vehicles and equipment.	0	
0095010	0	Platform w/Devices	0	
0098170	S	United States Registry Canadian Registry PackageRequires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	
Configu	ration			
0200700	S	Not Applicable Secondary Manufacturer	0	
Frame &	Equip	oment		
0514050	0	10-3/4" Steel Rails 385-402" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	903	58
0601500	0	Full Steel Inner Liner	1,827	80
0611250	0	Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket	330	
0611330	0	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	
0644090	0	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder	57	4
		installed crossmember.		

Deal CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

Sales Code	Std/ Opt	Description	\$ List	Weigi
Front A	kle & E	quipment		
1011890	0	PACCAR FX-20 Steer Ax le 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.	2,631	13
		The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1114030	0	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	652	11
1243050	0	Power Steering Sheppard HD94 Dual Gear For use with 16,000 to 20,000 lb. axle ratings.	1,604	8
1250250	0	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	213	
1354850	0	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still overlng dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	170	4
1380070	0	Greasable Front Spring Pins	71	
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	
1380490	0	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	0	
Rear Ax	le & E	quipment	-	
1523310	0	Dana Spicer DSH40 40,000 lb, High Performance 40 Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	500	17

Price Level: January 1, 2024 Deal: CAR specs Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

Sales Code	Std/ Opt	Description	\$ List	Weight
1603146	0	Watson-Chalin SL13 Slf-Strg Pusher	11,079	938
		13,500 Lb, Includes (1) Air Tank		
1607135	0	135in Pusher Axle Spacing	0	0
1015100		From Centerline of Forward Drive Axle		
1615180	0	PHP10 Iron PreSet PLUS Hubs, Cast Drums With 13.5K or 20K Self-Steering Pusher Axles	-285	0
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	C
1660000	0	Dust Shields For Cam Brakes, Drive Axle(s)	83	4
1673090	0	Separate Dash Controls, Cont Trac Full Lock	118	
		Dana Spicer or Meritor - Tandem or Tri-Drive Axles (Air Rocker Switch		
		occupies the space of two gauges for tandem axle and three gauges for tri-drive axle)		
1680450	0	Rear Brake Camshaft Reinforcement	130	
		Rear brake camshaft reinforcement helps guard against wear and		
		corrosion.		
1680490	0	Gusseted Cam Brackets, Drive Axle(s)	70	
1680500	0	SBM Valve	285	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		Full trucks require a spring brake modulation (SBM) system for		
		emergency braking application. This system requires an SBM valve		
		and a relay valve with spring brakes on the rear axles. The SBM valve		
		allows the foot valve to operate the rear axle spring brakes if a failure		
1680950	0	exists in the rear air system. Stability System Not Selected Or Not Available	-101	
1000330	J	Cubinty Cystem Not Colected of Not Available	-101	
1682710	S	Anti-Lock Braking System (ABS) 6S6M	0	
		ABS-6. Includes air braking system.		
1683235	0	Omit SmarTire TirePressure Monitoring	-446	
		System Next Gen TPMS		
1684200	S	Synthetic Axle Lubricant All Axles	0	
		Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD		
		FE75W-90 which provides customers performance advantages over		
		current synthetic lubricants with reduced gear wear and extended		
		maintenance intervals, resulting in increased uptime. In addition, the		
		lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending		
		component life.		
1685280	0	Lift Axle Regulator & Gauge LH Driver Seat	919	
		Lift axle regulator and gauge, left hand driver seat, with switch and		
		gauge in dash,		
1685465	0	Stowed Lifted Axle Lower To Maximize Body Clearance	0	
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7	0	
	-	Bendix Air Cam Rear Drum Brakes to fit all heavy haul, contruction,	_	
		refuse and highway truck and tractor applications. Includes Automatic		
		Slack Adjusters & Outboard Mounted Brake Drums.		
1687090	0	Diff Lock Tandem Axles	2,005	6

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete Date. December 28, 2023

eight	\$List	Description	Std/ Opt	Sales Code
		With Speed Interlock, Automatically Disengages Wheel Diff Lock at Speeds Above 25 mph.		
0	0	Ratio 3.36 Rear Axle	0	1703360
-59	707	Peterbilt Low Air Leaf 40,000 lb, 52in Axle Spacing, Light Weight	0	1821970
2	59	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	0	1922260
			& Equi	Engine &
465	13,759	X15 525@1900 GOV@1900 1850@1000 Performance Series (2024 Emissions)	0	2059212
		N21350 C121 64Maximum Accelerator Vehicle N21370 C128 64Maximum Cruise Control Speed N21460 C132 1400PTO Maximum Engine Speed N21520 C133 5Idle Shutdown Timer N21610 C188 39Idle Shutdown Cold Ambient A N21620 C189 60Idle Shutdown Intermediate A N21630 C190 80Idle Shutdown Hot Ambient Ai N21550 C206 35Idle Shutdown Percent Engine N21340 C209 120Maximum Vehicle Speed N21510 C225 YESIdle Shutdown with Parking B N21450 C231 NOGear Down Protection N21570 C233 NOIdle Shutdown Manual Overrid N21440 C234 NOEngine Protection Shutdown N21480 C238 NOCruise Control and Engine Br N21470 C239 NOCruise Control Auto-Resume N21430 C333 0Driver Initiated OverrideMax N21410 C334 0Driver Initiated Override Ma N21590 C382 YESIdle Shutdown Hot Ambient Au N21500 C395 0Green House Gas Automatic En N21530 C396 YESIdle Shutdown Warning Period N21540 C397 60Idle Shutdown Warning Period N21320 C399 120Green House Gas Vehicle Spee N21400 C400 252Driver Initiated Override Re N21420 C401 10Green House Gas Vehicle Spee		
0	0	VMUX Electronics Architecture	S	2091130
0	0	Engine Idle Shutdown Timer Enabled	S	2091305
0	0	Enable EIST Ambient Temp Overrule	0	2091315
0	0	Eff EIST NA Expiration Miles		2091372
0	0	Effective VSL Setting NA		2091640
0	0	Typical Operating Speed 68 MPH	0	2092017

99% Complete

Deal: CAR specs Printed On: 12/28/2023 8:05:27 AM

Date: December 28, 2023 Quote Number: QUO-1073394-Z6G8Q3

Sales Code	Std/ Opt	Description	\$ List	Weight
0000000		Downston in Online and for Polones	0	
2092033	0	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	(
2140200	0	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	
2140410	S	Engine Brake Controls Located on RH Column	0	
2140450	0	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	165	
2140660	0	CARB Emission Warranty	0	
2140700	S	EPA Engine Idling Compliance	0	
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	
2522090	0	PACCAR Premium Starter - X15 Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	464	
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	
2539720	S	Low Voltage Disconnect System	0	
2621000	0	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	537	
2723220	0	18.7 CFM Naturally Aspirated Air Compressor X15 Only	0	
2812170	0	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three- stage engine brake operation,	0	
2921120	0	PACCAR Fuel/Water Separator Extended Service	239	
2921220	0	Fuel Heat for Fuel Filter	54	
2921320	0	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture	66	

Deal: CAR specs
Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

ales ode	Std/ Opt	Description	\$ List	Weigh
		freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.		
3114270	S	High Efficiency Cooling System	0	
0111210	Ū	Cooling module is a combination of steel and aluminum components,	Ū	
		with aluminum connections to maximize performance and cooling		
		capability. Silicone radiator & heater hoses enhance value, durability, &		
		reliability. Constant tension band clamps reduce leaks. Chevron Delo		
		Extended Life Coolant (NOAT) extends maintenance intervals reducing		
		maintenance costs. Anti-freeze effective to -30 degrees F helps protect		
		the engine. Low coolant level sensor warns of low coolant condition to		
		prevent engine damage. Radiator Size by Model: 520 1202 sq in, 579		
		1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in,		
		389 HH 1604 sq in, 567 1379 sq in.		
3291680	S	(1) Air Cleaner Firewall Mounted	0	
0201000	U	Molded rubber air intake connections with lined stainless steel clamps	J	
		seal to prevent contaminants in air intake.		
3367240	0	Exhaust Dual SOC, LH SOC Stack	2,693	11
0001210	•	Aesthetic Only, DPF/SCR RH Under Cab, Single Module	2,000	• • •
3381790	0	Chrome Finish Over Elbows for Dual Exhaust	622	1
3301790 0		Requires DPF tool box right-hand under cab, and battery box left-hand		
		under cab.		
22272	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	
338/8/0	3			
3387880	0	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	242	
	o ssion	& Equipment		
3387880	0	& Equipment Allison 4500 RDS-P Transmission, Gen 6	242	
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series	24,013	
3387880 Transmi	o ssion	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle		
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear	24,013	
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial	24,013	
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip	24,013	
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be	24,013	
3387880 Transmi 4052970	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting	24,013	
3387880 Transmi 4052970 4210870	o ssion O	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	24,013	
3387880 Transmi 4052970	o ssion o	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings	24,013	
3387880 Transmi 4052970 4210870	o ssion o	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear	24,013	
3387880 Transmi 4052970 4210870	o ssion o	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated.	24,013	
3387880 Transmi 4052970 4210870	o ssion o	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint	24,013	
3387880 Transmi 4052970 4210870	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	24,013	52
3387880 Transmi 4052970 4210870	o ssion o	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control	24,013	52
3387880 Transmi 4052970 4210870	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO	24,013	52
3387880 Transmi 4052970 4210870 4211250	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control	24,013	
3387880 Transmi 4052970 4210870 4211250 4233910 4250660	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commericial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO. TC-571 Torque Converter	24,013 0 1,664 106	21
3387880 Transmi 4052970 4210870 4211250	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commericial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO. TC-571 Torque Converter	24,013 0 1,664	52
3387880 Transmi 4052970 4210870 4211250 4233910 4250660	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commericial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO. TC-571 Torque Converter Auto Neutral Activates With Parking Brake Auto Neutral helps improve jobsite safety by reducing the possibility of	24,013 0 1,664 106	21
3387880 Transmi 4052970 4210870 4211250 4233910 4250660	0 ssion 0 0	& Equipment Allison 4500 RDS-P Transmission, Gen 6 Rugged Duty Series RPL20 Driveline Interaxle Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commericial vehicles and are permanetely lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. RPL25 Driveline, 2 Midship Bearings Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. Provides a driveline that is permanently sealed and lubricated. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field. (1) Dash Mounted Single Acting EOH PTO Control Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO. TC-571 Torque Converter	24,013 0 1,664 106	21

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete Date

Date: December 28, 2023 Quote Number: QUO-1073394-Z6G8Q3

Sales Code	Std/ Opt	Description	\$ List	Weigh
		Dynamic Shift Sensing		
4252940	0	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and C02 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	(
4256740	0	Allison 6-Speed Configuration, Wide Ratio Gears Allison 4500 transmission only	0	(
4256920	0	Dash Mounted Push Button Shifter Available with Allison transmissions	148	
Air & Tra	ailer E	quipment		
4510210	0	Bendix AD-HF EP Air Dryer, Heater Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonly in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	160	(
4520420	0	Pull Cords All Air Tanks	4	
4540260	0	Dash Winch Brake Switch To Operate All Brakes (Truck & Trailer). A&E EOF On Moveable Xmbr.	370	1
4540420	S	Nylon Chassis Hose	0	
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air	0	
4543330	0	tanks installed. Polished Aluminum Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	244	
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	
4611930	0	Body Connections 5 BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	194	
Tires &	Wheel			
5058970	0	FF: MN 20ply 315/80R22.5 XZUS2 Efficiency Rating: Fair All-position, wide base single designed for significant weight and fuel savings in urban regional applications. Diameter = 42.9 inches; SLR =	953	9

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

ode	Opt	Description	\$ List	Weigl
		19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread.		
5156160	0	RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair	1,844	
5190008	S	Code-rear Tire Qty 08	0	
5220520	0	FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	506	-3
5320530	0	RR: Alcoa 89U647 22.5X9.00 High Polish Aluminum. Ultra ONE wheels with MagnaForce alloy.	1,972	-8
5390008	S	Code-rear Rim Qty 08	0	
5407640	0	FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	73	
5407660	0	RR: Mirror Polish Wheels, Outer Surface, Tandem Drive Mirror polish outer surface of outer wheels (4). Without chrome wheel nuts.	566	
5407700	0	PR: Mirror Polish Wheels, Outer Surface All pusher axles. Mirror polish outer surface of outer wheel.	283	
5410140	0	FF: Dura-Bright Finish Outer Surface of Outer Wheel, requires Polished Option	262	
5410160	0	RR: Dura-Bright Finish-Tandem Axle Outer Surface of Outer Wheel, requires Polished Option	524	
5410200	0	PR: Dura-Bright Finish All pusher axles - outer surface of outer wheel, requires polished option.	262	
5475498	0	PR: (2) MN 18ply 295/60R22.5 X Line Energy Z ETRTO; (1) self-steering pusher axle.	1,762	2
5482052	0	PR: (2) Alcoa 89U637 22.5X9.00 High Polish Aluminum, (1) self-steering pusher axle. Ultra ONE technology.	865	
Fuel Tar	nks			
5554220	υ	26" Aluminum 110 Gallon Fuel Tank LH WC	692	;
5602100	0	Location LH U/C 100 Gallon	0	
5650540	0	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	29	
5650810	0	Polish (1) Aluminum Fuel Tank	261	
5652830	0	Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps	83	
5652880	0	DEF Tank Mounted RH BOC You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel	0	

Deal: CAR specs Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

Sales Code	Std/ Opt	Description	\$ List	Weight
		distributors have chosen to standardize on DEF dispensing pumps oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting.		
5652990	0	DEF To Fuel Ratio 2:1 Or Greater	0	(
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	(
5760010	0	RH Tank None Furnished	-712	-80
Battery	Box &	Bumper		
6010670	0	Aluminum Space Saver Battery Box LH BOC Battery access from side	-235	-5
6030540	0	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete	288	
6034620	0	Heavy Duty Battery Box Step Reinforcement	71	i
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	
6122910	0	Steel Texas Style Bumper Chromed Steel Texas styled bumper chromed with two tow points.	1,023	
Cab & E	quipn			
6515770	0	Vocational 121 BBC Alum Cab and Metton Hood SFFA Stainless steel crown and grille with tilt assist.	3,931	-3
6540660	0	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	414	
6700000	S	No Sleeper Selected	0	
6800510	0	Fender Lips 2.25" Wide	786	
6911100	S	Peterbilt ST Driver Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standand	0	
6921140	0	vinyl finish - color coordinate with interior color. Peterbilt ST Passenger seat	381	
U32 1 14U	0	Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved	301	

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete Date: December 28, 2023

iales Code	Std/ Opt	Des cription	\$ List	Weigh
		passenger side ingress/egress for personal carog/luggage. Standand vinyl finish - color coordinate with interior color.		
6930580	0	Drivers Armrests - LH & RH	170	-
6930590	0	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	125	
6930800	0	Black Seat Color IPO Standard Color	0	
6939400	S	Air Ride Driver	0	
6939420	S	High Back Driver	0	-
6939470	S	Vinyl Driver	0	
6939500	0	Air Ride Passenger	0	
6939520	S	High Back Passenger	0	
6939570	S	Vinyl Passenger	0	
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button, audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	
7001520	S	Adjustable Steering Column - Till/Telescope	0	
7037130	S	Prestige Interior - Sterling Gray Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels. Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, rubber flooring, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in	0	
7210420	0	dash. Dark Window Tint IPO Standard Tint - Day Cab	30	
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	
7230060	S	1-Piece Curved Windshield	0	

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023 Quote Number: QUO-1073394-Z6G8Q3

Sales Code	Std/ Opt	Description	\$ List	Weight
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	0	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper,	978	0
7510060	0	Aero Rear View Mirror Housing, Bright Finish	330	3
7514010	0	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	314	3
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7610500	S	Air Horn Mounted Under Cab	0	0
7722120	0	ConcertClass, AM/FM, Weatherband, 3.5 Aux	415	10
7725740	0	Midlevel Speaker Package For Cab (4) Speakers	109	6
7728030	0	Radio Mute When In Reverse For automatic or automated transmission	0	0
7728040	0	Bluetooth Phone and Audio Requires USB Port	56	O
7728050	0	USB Port	56	C
7740130	0	Cobra 29 CB Radio Mounted Center Of Header With weatherband. Mounted in center of header, sound tracker & illuminated panel. Includes wiring, microphone clip, & speaker. Must select antenna(s) option.	366	11
7748150	0	(1) Antenna for Factory Installed or F/O CB Mounted LH cowl, low mount only, with antenna cable. Provides clear top of cab.	110	1
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and	0	0

Deal: CAR specs Printed On: 12/28/2023 8:05:27 AM

99% Complete Date: December 28, 2023

Sales Code	Std/ Opt	Description	\$ List	Weigh
		available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.		
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	
7852020	0	Cab Air Suspension	250	
7852050	0	Auto Reset Circuit Protection Daycab and Sleeper	19	
7900040	0	Fire Extinguisher, Ship Loose Hazmat approved UL listed/rated ABC.	55	
7900090	0	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	36	1
7901130	0	Backup Alarm (107 DB)	137	
8011410	0	Drive Axle #1 Front Oil Temperature Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	148	
8011420	0	Drive Axle #2 Rear Oil Temperature Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	175	
8011470	0	Engine Oil Temperature Gauge 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	57	
8011850	0	Transmission Oil Temperature (Main) Located in Digital Cluster Display.	28	
8021530	0	Air Suspension Pressure 1 Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6,	117	
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	
8070000	0	Disable Brake Light With Engine Brake	0	
8070110	0	(5) Additional Dash Switches with Wiring Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	211	
8070450	0	Engine PTO Hourmeter Gauge Located In Digital Cluster Display	0	
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	
8070830	0	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level,	0	

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

Sales Code	Std/ Opt	Description	\$ List	Weigh
		DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.		
8071900	0	Manifold Pressure Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	51	:
8076010	0	Pusher Axle Pressure 1 52mm Round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6.	120	
8110070	S	Headlights Projector Module Pod Fender mounted tum signals, projector module low beam, complex reflector high beam, pod mounted	0	
8120990	S	(5) Marker Lights, Aero LED On roof, visor, or fairing	0	
8133470	0	Switch & Wiring for F/O Beacon/Strobe Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	52	
8133900	0	None Furnished Stop/Tail/Backup Lights Available with full truck only, not available with tractor	-4 6	•
8134160	0	Self-Canceling Turn Signal	0	
Paint				
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0001EY BLACK N85500 CAB ROOF L0001EY BLACK N85300 FENDER L0001EY BLACK N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0001EY BLACK	0	
Shipping	g Dest	ination		
Options	Not S	ubject To Discount		
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	
9407147	0	Fuel Price Index Factor \$213 NET	213	
9408624	0	SmartLINQ RD - 3YR Sub Cummins Engines	499	
9408707	0	Base Warr: Emissions (CARB Operation) 5YR/350K MI - X15 PER/PRO Engine	3,495	
Miscella	neous			
9409001	S	Day Cab / Prestige Interior (DM)	0	

Deal: CAR specs

Printed On: 12/28/2023 8:05:27 AM

99% Complete

Date: December 28, 2023

Sales Std/
Code Opt Description Stist Weight

Promotions

Special Requirements

Special Requirement 1 0098170

Special Requirement 2 Special Requirement 3

Special Requirement 4

Order Comments

Total List Price (W/O Freight & Warranty & Surcharges)
Marketing and Service Support Fee
Prepaid Freight
Total Surcharge/Options Not Subject To Discount

Total Weight 19.295

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and <u>performance</u> data for <u>unpublished</u> options <u>may vary</u> from that <u>displayed</u> in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: January 1, 2024 99% Complete Date: December 28, 2023

Deal: CAR specs Quote Number: QUO-1073394-Z6G8Q3

Printed On: 12/28/2023 8:05:27 AM

rinted Un: 12/28/2023 8:05:27 AIVI

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address
New England Truck Center 156 Epping Road Exeter, NH 03833

Date	Estimate #		
2/15/2024	PB567LJ-W		

PO#

OP#

		PB567LJ-W		STOCK
Item	Description	Qty		Total
Chassis	2025 PETERBILT 567 LJ VIN# TBD FET INCLUDED		1	228,063.00
Bodies	2024 40TB-28' SERIAL# TBD		1	75,180.00
FET Payable	BODY FET		1	11,103.98
C-NC21	40 000 TB		1	0.00
C-4028	28' - 40 000 TB		1	0.00
C-NC46	COMPLETE EQUIPMENT		1	0.00
C-D415	5 CHAIN SLOTS PER SIDE (18 TOTAL FOR 25', 26', 27', 28', 29', 30')		1	0.00
C-D44-4	SINGLE ROW OF (4) EXTRA CHAIN SLOTS IN THE CENTER OF DECK		1	0.00
C-D6	WOODEN FLOOR (24' TO 30')		1	0.00
C-C3	FLAT TOP DECK WITH STAKE POCKET, WITHOUT REMOVABLE RAILS		1	0.00
C-L16	5 MARKER LIGHTS PER SIDE		1	0.00
C-T04-1	DP 20,000 LBS WITH 5/8" X 75' WIRE ROPE(STANDARD FOR 40 000-TB)		1	0.00
C-NC156	WINCH AIR FREE SPOOL ON LEFT HAND SIDE (NC)		1	0.00
C-NC30	75' STEEL WIRE ROPE		1	0.00
C-CR01	SWIVEL HOOK		1	0.00
C-NC25	TANDEM AXLE		1	0.00
C-12V	12V WIRING		1	0.00
C-E51	HEAVY DUTY TOW BAR T-BAR 4" X 4" (STD)		1	0.00
C-G20	GALVANIZED SUB-FRAME AND BUMPER		1	0.00
C-NC17	CLEAR MARKER LIGHT		1	0.00
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON BUMPER		1	0.00
C-NC11	LEVER CONTROL STANDARDS		1	0.00
C-S052	STAINLESS ON REAR BUMPER		1	0.00
C-G012	STABILIZER GRIP (30,000 & 40,000 LBS) (4X4)		1	0.00
C-L112-1	2 LED WORK LIGHTS ON TOP OF THE REAR BUMPER		1	0.00
		Total		

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address
New England Truck Center 156 Epping Road Exeter, NH 03833

Date	Estimate #
2/15/2024	PB567LJ-W

PO#

OP#

		PB567LJ-W		STOCK
ltem	Description	Qty		Total
C-A432	TRAILER HITCH & PINTLE HOOK ADAPTOR (4 HOLES) (T-BAR 4X4)		1	0.00
C-A1	STANDARD CHAIN RACK		1	0.00
C-A12	STD WINCH EMBEDDED IN CHAIN RACK		1	0.00
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON CHAIN RACK		1	0.00
C-NC40	CHAIN RACK NRC BLACK PAINT		1	0.00
C-S093	STAINLESS ON SIDES AND HEAD OF CHAIN RACK		1	0.00
C-L112-1	2 LED WORK LIGHTS UNDER THE TOP OF THE CHAIN RACK		1	0.00
C-LO6P	WIRELESS REMOTE CONTROL LODAR 6 BUTTONS		1	0.00
C-A421	RECOVERY ROLLER GUIDE (ROLLBACK)		1	0.00
C-S056	STAINLESS ON OIL TANK		1	0.00
C-NC110	WIRED TOWLIGHT ONLY		1	0.00
C-T6	TOUCHPAD WITH FUSELESS LIGHTING SYSTEM CONTROLLER		1	0.00
C-P-O	NO NEW CUSTOM REQUEST		1	0.00
C-PGAL-2	DECK GALVANIZED (OPTION FOR 24'-30' DECKS)		1	0.00
C-DISCLAIMER	CUSTOMER, FINAL PURCHASER OR END USER HAS BEEN INFORMED OF THE RISKS AND BENEFITS OF HOT DIP GALVANIZING (HDG) OF HIS NRC CAR CARRIER DECK		1	0.00
C-NC26	"BLACK POLYMER CONTROL BOXES (STANDARD)		1	0.00
C-RACK6	74" (1880MM) - HEIGHT ABOVE FRAME RAILS (C#6) UNCONFIGURABLE ITEMS		1	0.00
DESTTRANSPORT	DESTINATION TRANSPORT CHARGE		1	1,300.00
30/40TBINSTALL-IN	DEALER INSTALL WITH PTO, HOSE TRACK, STANDARD STOCK PAINT AND DETAIL		1	11,500.00
72AMBJUSTLB-INST	72" AMBER JUSTICE LIGHT BAR INSTALLED		1	2,450.00
TU824003-INST	60" BAWER STAINLESS TOOLBOX INSTALLED		2	3,403.20
		Total		

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address	
New England Truck Center 156 Epping Road Exeter, NH 03833	

Date	Estimate #		
2/15/2024	PB567LJ-W		

OP#			PO#
PB567LJ-W		STOCK	
Qty			Total

Item	Description	Qty	Total
Item	***PRICING BASED ON CURRENT DATA. FINAL PRICE WILL BE SET ONCE DEPOSIT IS RECEIVED AND BUILD SLOT SECURED.***	Qty	Total
		Total	
		Total	\$333,000.18

ONCE THE BUYER ACCEPTS THIS ORDER, THE BUYER'S DEPOSIT IS NOT REFUNDABLE UNLESS THE BUYER CANNOT TAKE DELIVERY OF SAID VEHICLE(S) FOR A REASON BEYOND THE BUYER'S CONROL. IN THAT EVENT, THE DEALER MAY, BUT WILL NOT BE REQUIRED TO, RETURN THE DEPOSIT TO THE BUYER, LESS ANY EXPENSES WHICH THE DEALER HAS INCURRED IN ACCEPTING AND PROCESSING THIS ORDER. THE BUYER'S FAILURE TO OBTAIN FINANCING BEFORE SCHEDULED DELIVERY IS NOT A REASON BEYOND THE BUYER'S CONTROL. THE BUYER WILL ALSO BE SUBJECT TO ANY PRICE INCREASES THAT ARE RECEIVED BY THE DEALER PERTAINING TO THE CHASSIS OR BODY. BY SIGNING THIS THE BUYER ACKNOWLEDGES HAVING READ AGREEING TO THESE TERMS AND CONDITIONS.



Terms & Conditions

- Once the buyer accepts this order, the buyer's deposit is not refundable unless the
 buyer cannot take delivery of the said vehicle(s) for a reason beyond the buyer's
 control. In that event, the dealer may, but will not be required to return the
 deposit to the buyer, less any expenses which the dealer has incurred in accepting
 and processing this order. The buyer's failure to obtain financing before scheduled
 delivery is not a reason beyond the buyer's control.
- The buyer will be subject to any price increase and or surcharge that are received by the dealer pertaining to the chassis or body.
- The buyer will be subject to any price increase on raw materials / parts that are incurred from the time of placing the order to the actual time of build and delivery of the unit(s).
- By signing this the buyer acknowledges having read and agreeing to these terms and conditions.

Date:	_	
Signature of Purchaser:		
Opp#	Chassis:	Body:
NETC Representative:		

"Everything Truck"