

156 Epping Road Exeter, NH 03833 800-261-7219

Stock Number: Peterbilt 589 - Galvy Deck 2026 Peterbilt 589

Details:

- 2025 NRC 40TB 28'
- Galvanized Deck and Subframe
- Lodar Remote
- > 20k Winch
- Cummins X15
- > 525HP
- Eaton RTLO189188 18-Speed
- Full Chassis / Body spec attached

Price: \$334,270



New England Truck Center 156 Epping Road Exeter, New Hampshire 03833 United States of America

MIKE LAMPERT

Vehicle Summary

	Unit	Chassis	
Model:	Model 589 Traditional	Fr Axle Load (lbs):	20000
Type:	Full Truck	Rr Axle Load (lbs):	40000
Description 1:	589 reg	G.C.W. (lbs):	60000
Description 2:	Clone of Chassis 730234		
•	Application	Road Conditions:	
Intended Serv.:	Wrecker	Class A (Highway)	100
Commodity:	Transportation Equipment	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
	Body	Class D (Off-Road)	0
Type:	Platform w/Devices	Maximum Grade:	6
Length (ft):	22	Wheelbase (in):	309
Height (ft):	9	Overhang (in):	60
Max Laden Weight (lbs):	3500	Fr Axle to BOC (in):	90.1
		Cab to Axle (in):	218.9
	Trailer	Cab to EOF (in):	278.9
No. of Trailer Axles:	0	Overall Comb. Length (in):	400
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
	Restrictions		
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		
Approved by:			

Note: All sales are F.O.B. designated plant of manufacture.

Price Level: January 1, 2024

Deal: 589 reg

Printed On: 11/14/2024 6:27:42 AM

99% Complete

Date: November 14, 2024 Quote Number: QUO-1129116-P3S9G0

Sales Code	Std/ Opt	Description	\$List V	Veight
Base Mo	CANAL MARKET			
0005891	S	Model 589 Traditional	222,533 1	4,820
0091170	0	Transportation Equipment	0	0
0093110	0	Wrecker Truck with recovery body used for recovering and towing stranded vehicles and equipment.	0	0
0095010	0	Platform w/Devices	0	0
0098170	S	United States Registry Canadian Registry PackageRequires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configur	ration			
0200700	s	Not Applicable Secondary Manufacturer	0	(
Frame &	Equip	oment		
0514050	0	10-3/4" Steel Rails 385-402" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	903	576
0601500	0	Full Steel Inner Liner	1,827	808
0611250	0	Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket	330	3
0611330	0	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	•
0611790	S	Aluminum Frame Rail Crossmembers Excludes suspension	0	
0644090	0	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	57	-6
0651090	0	Omit Rear Mudflaps and Hangers	-58	-2
Front Ax	le & E	quipment		
1011890	0	PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other	2,631	13
		vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.		
ice Level: .	lanuary		ate: November 1	4 20

99% Complete

Date: November 14, 2024

Deal, 589 reg Printed On: 11/14/2024 6:27:42 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
	1991—110 1	The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.		
1114030	0	Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	652	119
1243020	0	Power Steering Sheppard SD110 Dual Gear Steering vocational and heavy haul vehicles with front axle ratings of 16,000 to 18,000 lbs. in single gear applications. Glidekote splines on steering shaft extend service life of components.	1,896	123
1250250	0	Power Steering Reservoir Frame Mounted w/Cooler A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	213	2
1354850	0	PHP10 Iron PreSet PLUS Hubs - Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still overing dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	170	42
1380070	0	Greasable Front Spring Pins	71	0
1380290	0	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	Tenneco Shocks For Steer Axle Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380490	0	PACCAR FX Wide Track IPO Standard 71in KPI IPO 69in front axle for improved turning radius.	0	15
1391480	0	Pad Dust Shields for Air Disc Brakes; Front Axle Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	52	2
Rear Axi	le & E	quipment		
1523310	0	Dana Spicer DSH40 40,000 lb, High Performance 40 Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	500	179
1603146	0	Watson-Chalin SL13 SIf-Strg Pusher 13,500 Lb, Includes (1) Air Tank	11,079	938

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

Date: November 14, 2024 99% Complete

ales ode	Std/ Opt	Description	\$ List	Weigh
1607152	0	52in Pusher Axle Spacing	0	C C
		From Centerline of Forward Drive Axle		
1615180	0	PHP10 Iron PreSet PLUS Hubs, Cast Drums	-285	0
		With 13.5K or 20K Self-Steering Pusher Axles		
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	C
1660000	0	Dust Shields For Cam Brakes, Drive Axle(s)	83	4
1673090	0	Separate Dash Controls, Cont Trac Full Lock Dana Spicer or Meritor - Tandem or Tri-Drive Axles	118	
1680450	0	Rear Brake Camshaft Reinforcement	130	
1000430	O	Rear brake camshaft reinforcement helps guard against wear and corrosion.	130	,
1680490	0	Gusseted Cam Brackets, Drive Axle(s)	70	1595
1680500	0	SBM Valve	285	The Synthetic
		Full trucks require a spring brake modulation (SBM) system for		
		emergency braking application. This system requires an SBM valve		
		and a relay valve with spring brakes on the rear axles. The SBM valve		
		allows the foot valve to operate the rear axle spring brakes if a failure		
1000050		exists in the rear air system.	404	
1680950	0	Stability System Not Selected Or Not Available	-101	
1682710	S	Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	0	
1683235	0	Omit Tire Pressure Monitoring System	-446	
1684200	S	Synthetic Axle Lubricant All Axles	0	
1004200	3	· ·	U	
		Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over		
		current synthetic lubricants with reduced gear wear and extended		
		maintenance intervals, resulting in increased uptime. In addition, the		
		lubricant provides improved fluid flow to protect gears in extreme cold		
		conditions and withstand the stress from high temperatures, extending		
		component life.		
1685280	0	Lift Axle Regulator & Gauge LH Driver Seat	919	
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	_	Lift axle regulator and gauge, left hand driver seat, with switch and	0.10	
		gauge in dash.		
1685465	0	Stowed Lifted Axle Lower To Maximize	0	
		Body Clearance		
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7	0	
		Bendix Air Cam Rear Drum Brakes to fit all heavy haul, contruction,		
		refuse and highway truck and tractor applications. Includes Automatic		
		Slack Adjusters & Outboard Mounted Brake Drums.		
1687090	0	Diff Lock Tandem Axles	2,005	6
		With Speed Interlock. Automatically Disengages Wheel Diff Lock at		
		Speeds Above 25 mph.		
1703420	0	Ratio 3.42 Rear Axle	0	

Deal 589 reg

Printed On: 11/14/2024 6:27:42 AM

99% Complete

Date: November 14, 2024

les de	Std/ Opt	Description	\$ List	Weight
321970	0	Peterbilt Low Air Leaf 40,000 lb, 52in	707	-59
922260	0	Axle Spacing, Light Weight Dash Mtd Dump Switch with Indicator Light	59	2
322200	U	Dash mounted dump switch with indicator light for suspension.	59	
ngine &	Equi			10.200
059249	O	X15 525V@1900 GOV@2000 1850@1000 PROD SERIES (2024 EMISSIONS) N21350 C121 64Maximum Accelerator Vehicle N21370 C128 64Maximum Cruise Control Speed N21460 C132 1400PTO Maximum Engine Speed N21520 C133 5Idle Shutdown Timer N21610 C188 39Idle Shutdown Cold Ambient A N21620 C189 60Idle Shutdown Intermediate A N21630 C190 80Idle Shutdown Hot Ambient Ai N21550 C206 35Idle Shutdown Percent Engine N21340 C209 100Maximum Vehicle Speed N21510 C225 YESIdle Shutdown with Parking B	13,759	428
		N21450 C231 NOGear Down Protection N21570 C233 NOIdle Shutdown Manual Overrid N21440 C234 NOEngine Protection Shutdown N21480 C238 NOCruise Control and Engine Br N21470 C239 NOCruise Control Auto-Resume N21430 C333 0Driver Initiated OverrideMax N21410 C334 0Driver Initiated Override Ma N21590 C382 YESIdle Shutdown Hot Ambient Au N21500 C395 0Green House Gas Automatic En N21530 C396 YESIdle Shutdown Warning Period N21540 C397 60Idle Shutdown Warning Period N21320 C399 100Green House Gas Vehicle Spee N21400 C400 252Driver Initiated Override Re N21420 C401 10Green House Gas Vehicle Spee N21330 C402 0Green House Gas Vehicle Spee		
091120	S	EMUX Electronics Architecture	0	O
091305	S	Engine Idle Shutdown Timer Enabled	0	0
091315	0	Enable EIST Ambient Temp Overrule	0	0
091372		Eff EIST NA Expiration Miles	0	C
091640		Effective VSL Setting NA	0	(
092014	S	Typical Operating Speed 65 MPH	0	(
092032	0	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	(
140200	0	CARB Engine Idling Compliance	0	

Quote Number: QUO-1129116-P3S9G0

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
the second secon	9-17-18-46-13-44-4 <u>8-1</u>	PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.		
2140280	0	Locate Engine Idle Sticker on Bottom of Driver Door Lower Left Hand Position	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2140450	0	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	165	0
2140660	0	CARB Emission Warranty	0	0
2140700	S	EPA Engine Idling Compliance	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522090	0	PACCAR Premium Starter - X15 Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	464	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539410	0	Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	140	4
2539720	S	Low Voltage Disconnect System	0	0
2621090	S	HORTON ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723220	0	18.7 CFM Naturally Aspirated Air Compressor X15 Only	0	0
2812170	0	Intebrake (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three- stage engine brake operation.	0	0
2921120	0	PACCAR Fuel/Water Separator Extended Service	241	0
2921220	0	Fuel Heat for Fuel Filter	54	0
2921320	0	12V Heat for Fuel Filter Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3114270	S	High Efficiency Cooling System	0	0

Deal: 589 reg Printed On: 11/14/2024 6:27 42 AM

99% Complete

Date: November 14, 2024

ales Code	Std/ Opt	Description .	\$ List	Weight
Lar tening	yp t	Cooling module is a combination of steel and aluminum components,		
		with aluminum connections to maximize performance and cooling		
		capability. Silicone radiator & heater hoses enhance value, durability, &		
		reliability. Constant tension band clamps reduce leaks. Chevron Delo		
		Extended Life Coolant (NOAT) extends maintenance intervals reducing		
		maintenance costs. Anti-freeze effective to -30 degrees F helps protect		
		the engine. Low coolant level sensor warns of low coolant condition to		
		prevent engine damage. Radiator Size by Model: 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in,		
		389 HH 1604 sq in, 567 1379 sq in.		
3212030	S	(2) 15" Premium SS Air Cleaners Cowl Mounted	0	
32 12030	0	Slotted Stainless Steel Caps	U	•
3367240	0	Exhaust Dual SOC, LH SOC Stack	1,807	85
0007240	O	Aesthetic Only, DPF/SCR RH Under Cab, Single Module	1,007	0.
3387870	S	24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	(
		27 Th, C Dia Gine, Gloui Gout Ganapipo(6)		
3387880	0	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	242	4
Transmi	ssion	& Equipment		
1001000	0	Fatar BTI 000040B 40 Cmard	4 400	24
4021920	0	Eaton RTLO20918B 18-Speed	1,409	343
		Includes oil-to-water cooler, rear transmission support, direct shift		
		pattern. Synthetic lubricant to reduce friction, improve efficiency, &		
		extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life.		
		Torque limiting clutch brake. Forward ratios: LL-14.4, L-12.29, 1st-8.51,		
		2nd-7.26, 14th-1.00, 15th-0.86, 16th-0.73. Reverse ratios: R1-15.06,		
		R2-12.85, R3-4.03, R4-3.43		
4210280	0	1810 HD Driveline, 2 Midship Bearings	1,266	21
12 10200	Ü	4.5in x .180 wall tubing	,,	
4216590	0	1710 Driveline Interaxle	357	
		For tandem rear axles		
4233900	0	(1) Dash Mounted Single Acting EOA PTO Control	110	11103
		Electric-over-air (EOA), spec'ing PTO (power-take-off) control switch		
	Automocia de ave	does not ensure the PTO will fit.		Amelia de la composição d
4250800	0	Manual Shifter, Chrome	-290	
4321000	0	Self-Adjust Clutch	211	
4380220	0	Pre-Damped Clutch	167	
	-	Pre-damped feature consists of a set of small springs around the hub,		
		which dampen the engine torsional vibrations at idle speeds before they		
		can reach the transmission and cause gear rattle. Option required on		
		configurations specifying an ISX15 Family 1 engine and a manual		
		transmission with torque ratings of 1650 lb-ft torque or higher.		
Air & Tr	ailer E	quipment		
4510190	S	Bendix AD-HF Air Dryer, Heater	0	
		The state of the s		
		Bendix AD-HF air filters protects the life of your engine system and		

Quote Number: QUO-1129116-P3S9G0

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

ode	Std/ Opt	Description	\$ List	Weight
	©© (u • Le Men (dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.		
4520420	0	Pull Cords All Air Tanks	0	0
4540260	0	Dash Winch Brake Switch To Operate All Brakes (Truck & Trailer). A&E EOF On Moveable Xmbr.	370	17
4540420	S	Nylon Chassis Hose	0	0
4543330	0	Polished Aluminum Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	417	0
4543500	S	Aluminum Air Tanks Natural under box, painted Back of Cab	0	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
4611930	0	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	194	6
Tires &	Wheel	S	raw-	77
5058970	0	FF: MN 20ply 315/80R22.5 XZUS2 Efficiency Rating: Fair All-position, wide base single designed for significant weight and fuel	953	98
		savings in urban regional applications. Diameter = 42.9 inches; SLR = 19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread.		
5156160	0	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860	1,844	8
5156160 5190008	0 S	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D	1,844	8
	1987	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair Code-rear Tire Qty 08 FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers		(
5190008	S	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair Code-rear Tire Qty 08 FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating. RR: Alcoa 89U647 22.5X9.00 High Polish	0	-36
5190008 5220520	S	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair Code-rear Tire Qty 08 FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating.	506	-36
5190008 5220520 5320530	S 0	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair Code-rear Tire Qty 08 FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating. RR: Alcoa 89U647 22.5X9.00 High Polish Aluminum. Ultra ONE wheels with MagnaForce alloy.	0 506 1,972	-80
5190008 5220520 5320530 5390008	S O S	19.8 inches. Compares to Goodyear G289 WHA and Bridestone M860 tread. RR: MN 18ply 295/60R22.5 X Multi D Efficiency Rating: Fair Code-rear Tire Qty 08 FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating. RR: Alcoa 89U647 22.5X9.00 High Polish Aluminum. Ultra ONE wheels with MagnaForce alloy. Code-rear Rim Qty 08 FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without	0 506 1,972	

99% Complete

Date: November 14, 2024

Deal 589 reg Printed On: 11/14/2024 6:27:42 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
		All pusher axles. Mirror polish outer surface of outer wheel.		
5410140	0	FF: Dura-Bright Finish	262	0
		Outer Surface of Outer Wheel, requires Polished Option		
5410160	0	RR: Dura-Bright Finish-Tandem Axle	524	0
10.0		Outer Surface of Outer Wheel, requires Polished Option	and the second	
5410200	0	PR: Dura-Bright Finish	262	0
		All pusher axles - outer surface of outer wheel, requires polished		
	-	option.		
5475498	0	PR: (2) MN 18ply 295/60R22.5 X Line Energy Z	1,762	214
		ETRTO; (1) self-steering pusher axle.		
5482052	0	PR: (2) Alcoa 89U637 22.5X9.00 High Polish	865	98
		Aluminum, (1) self-steering pusher axle. Ultra ONE technology.		
Fuel Tan	ks			
5554190	0	26" Aluminum 100 Gallon Fuel Tank LH U/C	412	22
	_	Includes steps for cab access. Paddle handle filler cap with threadless	,,_	
		filler neck. Top draw fuel plumbing reduces chance of introducing air		
		into the fuel system during low fuel level conditions due to the central		
		placement of fuel pickup tube. Wire braid fuel lines increase durability	·	
- 11		& reduce potential for leaks.		
5602100	0	Location LH U/C 100 Gallon	0	0
5650540	0	Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only	29	0
5650810	0	Polish (1) Aluminum Fuel Tank	261	0
5652830	0	Polish All Fuel / Hydraulic Tank Straps	83	0
0002000	Ū	Does not apply to rectangular DEF tank straps	05	U
5652890	0	DEF Tank Mounted LH BOC	0	0
0002000	O	Models 220 and 520 mounted left hand back-of-cab.	U	U
5652990	0	DEF To Fuel Ratio 2:1 Or Greater	0	0
0002000		DEL TOTUET NAUO 2.1 OF Greater	0	U
5653000	0	Polished Stainless Steel Cover For DEF Tank	275	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
5760010	0	RH Tank None Furnished	-712	-86
Battery E	30x &	Bumper		
6010780	0	Aluminum Space Saver Battery Box RH BOC	-735	-60
		Battery access from side		35
6030540	0	Polish Battery/Tool Box(s)	288	0
		Aftertreatment Cab Entry, complete		
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry	0	0
		Aftertreatment right-hand under cab step. DPF/SCR for diesel engines,		
		catalyst for natural gas engines. On Models 579 specifying chassis		
		fairings, the box is aerodynamic.		
6122910	0	Steel Texas Style Bumper Chromed	1,354	-6

99% Complete

Date: November 14, 2024

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

ales ode	Std/ Opt	Description	\$ List	Weigh
Propagation (ACC)	Parties and Parties	Two tow points.		
6132450	0	Heavy Duty External Tow Eye	578	42
		IPO Standard, N/A With FETPO	55	
Cab & E	quipm	ent		
6510210	s	Aluminum Cab, 121" BBC Alum Hood SFFA	0	(
		With polished crown and spring tilt assist.		
6540660	0	SmartSound Cab Insulation Package Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	414	
6700000	S	No Sleeper Selected	0	
6800360	0	Rubber Fender Lips 2" Wide	786	04/11
6911740	0	Peterbilt LX Driver	210	- 100 P
30.11.10		Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout, vinyl bellows over suspension, Requires folding armrests, side and back storage pocket. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress	210	
6921130	0	into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standard with fabric/vinyl finish - color coordinated with interior color	0.40	
0921130	0	Peterbilt LX Passenger seat Peterbilt LX Air seat, high height backrest, adjustable seat track length, 2 chamber lumbar support, premium suspension with adjustable damping, auto leveling, exit air dump, memory for sitting height, fore-aft isolator with lockout and vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal cargo/luggage. Standard with fabric / vinyl - color coordinated with interior color.	646	2
6930580	0	Drivers Armrests - LH & RH	170	19.5
6930590	0	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	125	
6930800	0	Black Seat Color IPO Standard Color	0	
6939400	S	Air Ride Driver	0	- (A)
6939420	S	High Back Driver	0	
6939450	0	Leather Driver	320	277
6939500	0	Air Ride Passenger	0	
6939520	S	High Back Passenger	0	

99% Complete

Deat: 589 reg Printed On: 11/14/2024 6;27:42 AM

Date: November 14, 2024 Quote Number: QUO-1129116-P3S9G0

Sales Code	Std/ Opt	Description	\$ List	Weight
6939550	0	Leather Passenger	320	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001630	0	Premium Steering Wheel with Multi Function Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	19	5
7033550	S	Premier Interior - Alpine Gray	0	0
7040150	0	Rubber Floor IPO Carpet (Black Only) Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-92	Ō
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	C
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	C
7230060	S	1-Piece Curved Windshield	0	
7230360	S	Power Door Locks and Power Window Lifts Standard	0	(
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	(
7410160	0	Outside Sunvisor - Stainless Steel V-Style Day cab / low roof sleepers.	874	8
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	(
7516000	S	Stainless Steel Mirrors 7"X18" Heated & Motorized West Coast Style	0	(
7560860	S	(2) Convex 8 Inch Heated SSTL Mirrors Mounted under mirror brackets	0	(
7610500	S	Air Horn Mounted Under Cab	0	(
7722120	0	ConcertClass, AM/FM, Weatherband, 3.5 Aux	415	10
7725740	0	Midlevel Speaker Package For Cab (4) Speakers	109	6
7728040	0	Bluetooth Phone and Audio Requires USB Port	56	(
7728050	0	USB Port	56	(
7740130	0	Cobra 29 CB Radio Mounted Center Of Header With weatherband. Mounted in center of header, sound tracker & illuminated panel. Includes wiring, microphone clip, & speaker. Must select antenna(s) option.	366	11

Quote Number: QUO-1129116-P3S9G0

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

Sales Code	Std/ Opt	Description	\$ List	Weight
7748320	0	(2) 48" CB Antennas	77	1
7748500	0	CB Antenna Mounting, LH Mirror	20	0
7748510	0	CB Antenna Mounting, RH Mirror	20	0
7788335	S	Global Telematics Hardware	0	0
7788345	0	Telematics HW Instl But SmartLINQ Dsbld	0	0
7850555	0	Dual USB Charging Port	217	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	0	Cab Air Suspension	153	0
7900040	0	Fire Extinguisher, Ship Loose Hazmat approved UL listed/rated ABC.	55	7
7900090	0	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	36	13
7901130	0	Backup Alarm (107 DB)	137	3
8011470	0	Engine Oil Temperature Gauge 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	57	0
8011800	0	Drive Axle #1 Front Oil Temperature Gauge Located in Digital Cluster Display.	126	C
8011810	0	Drive Axle #2 Rear Oil Temperature Gauge Located in Digital Cluster Display.	135	C
8021530	0	Air Suspension Pressure 1 Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6.	117	C
8021800	S	Air Filter Restriction Pressure Gauge Located in Digital Cluster Display	0	(
8022160	0	Fuel Filter Restriction Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	209	C
8070000	0	Disable Brake Light With Engine Brake	0	C
8070110	0	(5) Additional Dash Switches with Wiring Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch.	211	2
8070200	0	Tractor Brake Application Gauge	149	C

Sales Code	Std/ Opt	Description	.\$ List	Weight
		52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.		
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	S	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.		0
8071340	0	Bright Bezel Gauges	39	Ō
8071900	0	Manifold Pressure Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	51	2
8076010	0	Pusher Axle Pressure 1 52mm Round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6.	120	0
8111140	S	Headlights Projector Module Pod Integral Turn Signals	0	0
8121170	0	(5) Marker Lights, Bus LED Bullet		0
8133115	0	Marker Switch Wiring FO Auxiliary Light The Marker Switch (located on the D-Panel) and wiring will be provided for furnish-by-owner auxiliary lighting underneath the cab/sleeper. For the models 567 and 579, a maximum of 10 amps is allowed. For the model 589, a maximum of 10 amps is allowed without the order of option 8133120.		2
8133120	0	Marker Switch Wiring FO Auxiliary Light The Marker Switch (located on the D-Panel) and wiring will be provided for furnish-by-owner auxiliary lighting on the dual air cleaners. A maximum of 10 amps is allowed without the order of option 8133115.	110	2
8133470	0	Switch & Wiring for F/O Beacon/Strobe Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	52	2
8134160	0	Self-Canceling Turn Signal	0	C
8140120	0	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	46	g
Paint				
8500710	0	Standard Paint Color Selection	-200	C
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE	0	O

Deal: 589 reg Printed On: 11/14/2024 6:27:42 AM

Date: November 14, 2024 99% Complete

Sales Code	Std/ Opt	Description	\$ List	Weight
Emily Market Market		N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE		2.00 mm
Shippin	g Dest	ination		
Options	Not S	ubject To Discount	0.000	
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0
9407147	0	Fuel Price Index Factor \$21 NET	21	0
9408558	0	Prognostic Connection Fee	100	0
9408707	0	Base Warr: Emissions (CARB Operation) 5YR/350K MI - X15 PER/PRO Engine	3,495	0
Miscella	neous		. 11.00	
9409030	0	Day Cab / Premier Interior (DR)	0	0
9409079	0	State Of Registry: New Hampshire	0	0
9409749	0	2024 Series Emissions Engine	0	0

Promotions

Special Requirements

Special Requirement 1 0098170

Special Requirement 2

Special Requirement 3

Special Requirement 4

Order Comments

Total List Price (W/O Freight & Warranty & \$286,577 Surcharges)

Marketing and Service Support Fee\$1,495Prepaid Freight\$3,525Total Surcharge/Options Not Subject To Discount\$3,616

Total Weight (lbs) 19,174

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information

Price Level: January 1, 2024

Deal: 589 rea

Printed On: 11/14/2024 6:27:42 AM

99% Complete

Quote Number: QUO-1129116-P3S9G0

Page 15 of 16

Shipping Destinations

Intermediate Destination: NONE

Final Destinations	40 00 000	Quantity

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

W W Willett delt	center teom
Name / Addr	ess
New England Tr	uck Center
156 Epping Roa	
Exeter, NH 0383	
ı	

Date	Estimate #	
12/10/2024	PB589-GLV	

OP#	PO #	Rep
PB589-GLV	STOCK	

ltem	Description	Qty	Total
Chassis	2025 PETERBILT 589 VIN# TBD FET INCLUDED	1	232,986.00
Bodies	2025 NRC 40TB-28' SERIAL# TBD	1	71,145.00
FET Payable	BODY FET	1	10,712.58
C-NC21	40 000 TB	1	0.00
C-4028	28' - 40 000 TB	1	0.00
C-NC46	COMPLETE EQUIPMENT	1	0.00
C-D415	5 CHAIN SLOTS PER SIDE (18 TOTAL FOR 25', 26', 27', 28', 29', 30')	1	0.00
C-D44-4	SINGLE ROW OF (4) EXTRA CHAIN SLOTS IN THE CENTER OF DECK	1	0.00
C-DO	1/4" STEEL CHECKER PLATE (STANDARD FOR 40 000-TB)	1	0.00
C-C3	FLAT TOP DECK WITH STAKE POCKET, WITHOUT REMOVABLE RAILS	1	0.00
C-B3S	3" HIGH X 9" SPACING (STANDARD FOR 30 000-TB AND 40 000-TB)	1	0.00
C-L16	5 MARKER LIGHTS PER SIDE	1	0.00
C-T04-1	DP 20,000 LBS WITH 5/8" X 75' WIRE ROPE(STANDARD FOR 40 000-TB)	1	0.00
C-NC156	WINCH AIR FREE SPOOL ON LEFT HAND SIDE (NC)	1	0.00
C-NC30	75' STEEL WIRE ROPE	1	0.00
C-CR01	SWIVEL HOOK	1	0.00
C-CTR01	EXTRA FOR TRI-AXLE BODY	1	0.00
C-NC172	PAIR W/ ANOTHER KIT FOR SHIPPING TO DEALER ON A FLAT DECK TRAILER WITHIN NORTH AMERICA.FREIGHT NOT INCLUDED. FCA NRC FACTORY.	1	0.00
C-12V	12V WIRING	1	0.00
C-E51	HEAVY DUTY TOW BAR T-BAR 4" X 4" (STD)	1	0.00
C-G20	GALVANIZED SUB-FRAME AND BUMPER	1	0.00
C-NC17	CLEAR MARKER LIGHT	1	0.00
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON BUMPER	1	0.00
		Total	

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address	
New England Truck Center 156 Epping Road Exeter, NH 03833	

Date	Estimate #	
12/10/2024	PB589-GLV	

OP#	PO#	Rep
PB589-GLV	STOCK	

Item	Description	Qty	Total
C-NC11	LEVER CONTROL STANDARDS	1	0.00
C-S052	STAINLESS ON REAR BUMPER	1	0.00
C-G012	STABILIZER GRIP (30,000 & 40,000 LBS) (4X4)	1	0.00
C-L112-1	2 LED WORK LIGHTS ON TOP OF THE REAR BUMPER	1	0.00
C-A432	TRAILER HITCH & PINTLE HOOK ADAPTOR (4 HOLES) (T-BAR 4X4)	1	0.00
C-A1	STANDARD CHAIN RACK	1	0.00
C-A12	STD WINCH EMBEDDED IN CHAIN RACK	1	0.00
C-L118	8 X 4 1/2" LIGHT (6 RED (STOP-FLASH) / 2 BACKUPS) - ON CHAIN RACK	1	0.00
C-NC40	CHAIN RACK NRC BLACK PAINT	1	0.00
C-S093	STAINLESS ON SIDES AND HEAD OF CHAIN RACK	1	0.00
C-L112-1	2 LED WORK LIGHTS UNDER THE TOP OF THE CHAIN RACK	1	0.00
C-LO6P	WIRELESS REMOTE CONTROL LODAR 6 BUTTONS	1	0.00
C-A421	RECOVERY ROLLER GUIDE (ROLLBACK)	1	0.00
C-S056	STAINLESS ON OIL TANK	1	0.00
C-NC110	WIRED TOWLIGHT ONLY	1	0.00
C-T6	TOUCHPAD WITH FUSELESS LIGHTING SYSTEM CONTROLLER	1	0.00
C-P-O	NO NEW CUSTOM REQUEST	1	0.00
C-DISCLAIMER	CUSTOMER, FINAL PURCHASER OR END USER HAS BEEN INFORMED OF THE RISKS AND BENEFITS OF HOT DIP GALVANIZING (HDG) OF HIS NRC CAR CARRIER DECK	1	0.00
C-NC26	"BLACK POLYMER CONTROL BOXES (STANDARD)	1	0.00
C-RACK6	74" (1880MM) - HEIGHT ABOVE FRAME RAILS (C#6)	1	0.00
C-PGAL-2	DECK GALVANIZED (OPTION FOR 24'-30' DECKS)	1	0.00
	UNCONFIGURABLE ITEMS		
DESTTRANSPORT	DESTINATION TRANSPORT CHARGE	1	1,300.00
30/40TBINSTALL-IN	DEALER INSTALL WITH PTO, HOSE TRACK, STANDARD STOCK PAINT AND DETAIL	1	11,500.00
		Total	

Quote

156 Epping Rd. Exeter, NH 03833 (603)778-8158

www.netruckcenter.com

Name / Address	
New England Truck Center 156 Epping Road Exeter, NH 03833	

Date	Estimate #
12/10/2024	PB589-GLV

OP#	PO#	Rep
PB589-GLV	STOCK	

Item	Description	Qty	Total
72AMBJUSTLB-INST MX701818.KM-INST	72" AMBER JUSTICE LIGHT BAR INSTALLED 70" RC TOOLBOX, ALUMINIUM BOX, STAINLESS STEEL DOOR INSTALLED	1 2	2,450.00 4,176.52
	PRICING BASED OFF OF CURRENT PRICING, SUBJECT TO CHANGE CLOSER TO BUILD DATE		
		Total	\$334,270.10

ONCE THE BUYER ACCEPTS THIS ORDER, THE BUYER'S DEPOSIT IS NOT REFUNDABLE UNLESS THE BUYER CANNOT TAKE DELIVERY OF SAID VEHICLE(S) FOR A REASON BEYOND THE BUYER'S CONROL. IN THAT EVENT, THE DEALER MAY, BUT WILL NOT BE REQUIRED TO, RETURN THE DEPOSIT TO THE BUYER, LESS ANY EXPENSES WHICH THE DEALER HAS INCURRED IN ACCEPTING AND PROCESSING THIS ORDER. THE BUYER'S FAILURE TO OBTAIN FINANCING BEFORE SCHEDULED DELIVERY IS NOT A REASON BEYOND THE BUYER'S CONTROL. THE BUYER WILL ALSO BE SUBJECT TO ANY PRICE INCREASES THAT ARE RECEIVED BY THE DEALER PERTAINING TO THE CHASSIS OR BODY. BY SIGNING THIS THE BUYER ACKNOWLEDGES HAVING READ AGREEING TO THESE TERMS AND CONDITIONS.



Terms & Conditions

- Once the buyer accepts this order, the buyer's deposit is not refundable unless the
 buyer cannot take delivery of the said vehicle(s) for a reason beyond the buyer's
 control. In that event, the dealer may, but will not be required to return the
 deposit to the buyer, less any expenses which the dealer has incurred in accepting
 and processing this order. The buyer's failure to obtain financing before scheduled
 delivery is not a reason beyond the buyer's control.
- The buyer will be subject to any price increase and or surcharge that are received by the dealer pertaining to the chassis or body.
- The buyer will be subject to any price increase on raw materials / parts that are incurred from the time of placing the order to the actual time of build and delivery of the unit(s).
- By signing this the buyer acknowledges having read and agreeing to these terms and conditions.

Date:	_	
Signature of Purchase	r:	
Opp#	Chassis:	Body:
NETC Representative:		

"Everything Truck"